

## COOEE 3 CORDLESS TABLE LAMP

















Anodised **Silver**Aluminium



Lacquered Real Brass



Lacquered **Real Copper** 



Anodised **Sandblasted Bronze**Aluminium



Anodised **Sandblasted Black**Aluminium



Handling Accessory **6 Lamp Carrier**(Optional)













## **COOEE 3 - Technical Description**

The Cooee 3 rechargeable battery table lamp features a slim durable metal body and an internally ribbed conical diffuser providing soft ambient side and downlight. The lamp is fitted with a 1W 95+ CRI LED for superior colour rendering. Digital 3 step dimming.

Designer Peter Ellis, Tammy Chiew

Year of Design 2013

Lamp Type Sidelight & Downlight

IP Rating IP52

Dimensions 220mm x 97mm


(8½") x (3½")

Weight 0.28 kg / 0.61 lb

Approvals & Standards CE, CSA, C-Tick, FCC, RoHS, SASO

EU Energy Regulation Exempt - LED lamps operate on batteries

Awards IDA Design Award GOLD Winner 2013



Туре	Battery	Cells	Charge Time	Light Source Option	Colour Temperature (Kelvin)		ating Tir al mode Med	me (hours) e Low	Brightnes (lumens)	ss CRI*	Bulb Life (Hours)
UNO	Panasonic Li-ion 3.7V 2900mAh	1	5.5hrs	1W LED Warm White (Standard)	2600k	13	35	130	68+	95+	50,000+
		1	5.51115	IW LED Walli Wille (Stalldard)	2000k	13	33	130	001	95+	50,000±
				1W LED Warm Candle White (Option	onal) 1800k	13	35	130	58+	93+	50,000+
	500+ cycles										
COLOUR RENDERING INDEX (CRI)				The quantitative measure of the ability of a light source to reproduce the colors of various objects faithfully in comparison with an ideal or natural light source. The highest possible CRI is 100.							
POWER SOURCE				100 - 240V Switch-Mode Electronic Power Supply Approved for worldwide usage supplied with appropriate mains electric plug type							

## **Recharging Options**



Single Lamp Charger 1 Lamp



Small Recharging Tray **4 Lamps** 



Large Recharging Tray 12 Lamps



Small Recharging Station **24 Lamps** 



Medium Recharging Station **36 Lamps** 



Large Recharging Station **48 Lamps** 









