

BATTERY POWERED

CORDLESS LED PRO LANTERN

PL-48W-G1









4 CONFIGURATIONS: 360°, 180°, SPOTLIGHT, WARNING LIGHT





EXCELLENT PORTABILITY WITH A MULTI-ANGLE HANDLE

> 2 HANGING ? STYLES AVAILABLE





















LED SPECIFICATIONS

Power Consumption	48W
Fixture Weight	5.2 lbs (2.35 kg)
Fixture (L"x W")	6.62 x 12.48
Lamp Life (Hrs)	50,000 Hrs
CRI	≥80
IP Level	IP54
Spec LED Wattage (W)	Philips Lumileds 48W
Luminous Flux (Lumen)	4,000 Lumens
Color Temperature	5,000K
Certification	CUL/UL/CE/ROHS

BATTERY PERFORMANCE

TRIPOD ADAPTER FOR FAST AND SECURE


ATTACHMENT

Run Time(Hrs)	Max Brightne	ess Min Brightness
360°:	2.5 Hrs	25 Hrs
180°:	5 Hrs	50 Hrs
Flashlight:	9.4 Hrs	90 Hrs
SOS:	16 Hrs	150 Hrs
Charging Time		8 Hr
Battery Capacity		14.8V/7800m Ah
Operation Temp		14° F ~ 104° F
USB Output Parame	eter	5V/2A
Warranty	La	antern: 2Y,Battery: 1Y

VOLTERREX

Powered by ISM Lighting













ACCESSORIES









VOLTERREX™

TRIPOD BAG

RECHARGEABLE LED PRO LANTERN LIGHTING DIAGRAM

Ground Coverage of Illumination: Footcandles/Lux (fc/lx) vs. Distance (ft)





CHARGING FEATURES




- Charge Electronics via USB
- Utilize Built-in Battery for Portability
- Plug in Power Cord When Necessary



CONTACT

Volterrex powered by ISM Lighting



www.volterrex.com

300 Wampanoag Trail, Riverside, RI 02915



info@ismlighting.com

