

# **150W LED**

**BALLOON LIGHT KIT** 

VT-150-G2





HIGH LUMEN OUTPUT OF 19,500LM



**CARRY BAGS INCLUDED** 



MULTIPLE MOUNTING **OPTIONS INCLUDED** 



6FT / 2-STAGE **ADJUSTABLE MAST** 



RF REMOTE DOZENS **OF SETTINGS** 



ADAPTER SUPPORTED FOR EASY AND SECURE **ATTACHMENT** 



POWER MULTIPLE UNITS BATTERY PACK



360 DEGREE GLARE FREE 360 DEGREE GE .

DIFFUSED LIGHT





#### **SPECIFICATIONS**

Fixture Design	8-Sided e	xtrusion + Top panel
Total Wattage (W)		150W
Voltage (V)		AC 110-240V
Frequency (Hz)		50/60Hz
Operating Amps (A)		1.25A
Spec   LED Wattage (W)		Samsung   150W
Luminous Flux (Lumen)		19,500 Lumens
Color Temperature (Kelvin)		5,000K
Color Rendering Index (CRI)		>80
Lamp Life (Hrs)		50,000 Hrs

#### **DIMENSION & WEIGHT**

Diffuser Inflated (L"x W"x H")	5.7 x 5.7 x 9.8 (40 x 40 x 25 cm)
Fixture Weight	7.15 lbs (3.24 kg)
Fixture (L"x W"x H")	7 x 7 x 13 (18 x 18 x 33 cm)
Power Cable	15' ft (457 cm) SJOW 3*18 AWG CORE G US Stnd Plug
Tripod Dimensions (Collap	
Tripod Dimensions (Extend	ded) 79 in. (198 cm)
Tripod Weight	7.1 lbs (3.2 kg)
Tripod Footprint (L"xW"xH")	31 x 31 x 78 (79 x 79 x 198 cm)
Ingress Protection	IP44
Safety Certifications	UL, CE, FCC, RoHs

## **EFFORTLESS LIGHTING SETUP**

































### **150W LIGHT KIT POLAR LIGHTING DIAGRAM**

Ground Coverage of Illumination: Footcandles/Lux (fc/lx) vs. Distance (ft)















www.volterrex.com

info@ismlighting.com

300 Wampanoag Trail, Riverside, RI 02915

