



SOFT PLEAT CEILING LIGHT

MEASUREMENTS

20cm diameter / 12cm height

30cm diameter / 12cm height

MATERIALS

Iron, Acrylic

POWER USAGE

90-260V

LED LIFESPAN

50,000+ hours

DIMMABLE

Three-color dimming

LIGHT SOURCE

Integrated LED (fully built into the fixture and cannot be replaced)

WEIGHT

0.05KG

LIGHTCOLOR TEMPERATURE

3000 - 6000K

IMPORTANT SAFETY INFORMATION:

1. Turn off the power at the circuit breaker or fuse box before installation.
2. For safety and to ensure compliance with local electrical codes, it is recommended that installation be carried out by a qualified electrician or an experienced installer.
3. Handle with care. The iron and acrylic material are delicate and requires careful attention.

INSTALLATION

- Turn off power at the main circuit breaker.
- Secure the ceiling plate using the provided screws. Ensure it's level and firmly attached to support the weight (0.05KG).
- Connect the fixture wires to the ceiling wires: black (live) to black, white (neutral) to white, and green/yellow (ground) to the ground wire. Use wire connectors to secure.
- Attach Soft Pleat Ceiling Light to the mounted ceiling plate.
- The LED light source is pre-installed, so no additional installation is needed.
- Restore power and test the lighting.

ADDITIONAL TIPS

Maintenance: Clean the lamp regularly with a soft, dry cloth to remove dust. Avoid using harsh cleaning agents to protect the delicate iron and acrylic material.

NOTE

If you have any additional questions or requests, feel free to contact us via our contact page. You can easily place orders for our items via our website.