



LT1 2500K

March 2023
1/1

Specifications

Product Codes	2500KN: natural gas / 2500KP: propane
Product type	Direct Vent, Zero Clearance
Input (BTU)	Natural gas: 34,000 / 20,000 Propane: 34,000 / 22,000
Vent Outlet	4 x 6-5/8" co-axial. Top or Rear outlet.
Venting System	Co-axial 4 x 6-5/8", Co-Linear 3x4. Maximum horizontal without rise: 18".
Gas Convertible	Yes
Valve	GV60
Control	Valor10 remote control; Remote Battery & Wall Switch Kit included
Batteries	Fireplace: 4xAA in Remote Battery & Wall Switch Kit; 3xAAA in Remote control handset
Electrical	Included, via V-module to operate remote control receiver, lighting, and (optional) wifi
Lighting	Yes, requires 2x G6.35 35W halogen bulbs (included)
Wifi	¹ Optional. Operated by Valor10 application on smartphone.
Fan (Blower)	No
HeatShift	Mandatory. 5" outlets at fireplace. Uses any LDK kits except LDK8 30" plenum.
Liners	Fluted black, Plain black, Reflective glass
Fuel Beds	Logs: Driftwood, Splitwood, Birch, Murano Glass, or Rock and Shale
Fronts / Trims	Clean Install Kit or Linear 1" Finishing Trim
Outdoor Installation	Yes, with no electrical power connection. Requires GV60CKO Conversion kit
Comments	¹ Optional Wifi requires V-module and electrical power