


# Fast assembly concealed hinge

- ▶ Mounting plates with direct height adjustment
- ▶ For Sensys, Novisys and Intermat


## "Hettich Direkt" cross mounting plate with locating pin and special screws



- ▶ For  $\varnothing 5 \times 7.5$  mm holes
- ▶ Quality classification under EN 15570, Level 2
- ▶ Hole spacing 32 mm
- ▶ Half overlay door, from 15 mm side panel thickness
- ▶ Direct height adjustment  $\pm 2$  mm
- ▶ Steel nickel plated

Hole line distance LR mm	Order no. / Distance D mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 065	9 075 066	9 075 067	9 075 068	50 ea.
37	9 071 650	9 071 651	9 071 652	9 071 653	200 ea.


## Linear mounting plate for screwing on



- ▶ For  $\varnothing 3.5 \times 16$  mm countersunk screws
- ▶ Quality classification under EN 15570, Level 3
- ▶ Direct height adjustment  $\pm 2$  mm
- ▶ Steel nickel plated

Hole line distance LR mm	Order no. / Distance D mm		PU
	1.5	3.0	
20	9 117 341	9 117 342	50 ea.
20	9 308 078	9 308 079	200 ea.

## Linear mounting plate for pressing in



- ▶ For  $\varnothing 10 \times 12$  mm drillings
- ▶ Quality classification under EN 15570, Level 3
- ▶ Direct height adjustment  $\pm 2$  mm
- ▶ Steel nickel plated

Hole line distance LR mm	Order no. / Distance D mm		PU
	1.5	3.0	
20	9 117 344	9 117 388	50 ea.
20	9 308 080		200 ea.