


Fast assembly concealed hinge

- ▶ Mounting plates with direct height adjustment
- ▶ For Sensys, Novisys and Intermat


Cross mounting plate with premounted chipboard screws



- ▶ For holes with max. \varnothing 2.5 mm
- ▶ Quality classification under EN 15570, Level 3
- ▶ Hole spacing 32 mm
- ▶ Direct height adjustment \pm 2 mm
- ▶ Steel nickel plated

Hole line distance LR mm	Order no. / Distance D mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 085	9 075 086	9 075 087	9 075 088	50 ea.
37	9 071 670	9 071 671	9 071 672	9 071 673	200 ea.


Cross mounting plate with premounted Euro screws



- ▶ For $\varnothing 5 \times 12$ mm holes
- ▶ Quality classification under EN 15570, Level 3
- ▶ Hole spacing 32 mm
- ▶ Direct height adjustment \pm 2 mm
- ▶ Steel nickel plated

Hole line distance LR mm	Order no. / Distance D mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 080	9 075 081	9 075 082	9 075 083	50 ea.
37	9 071 665	9 071 666	9 071 667	9 071 668	200 ea.

Cross mounting plate with premounted Euro screws



- ▶ For $\varnothing 5 \times 8$ mm holes
- ▶ Quality classification under EN 15570, Level 3
- ▶ Hole spacing 32 mm
- ▶ Half overlay door, from 16 mm side panel thickness
- ▶ Direct height adjustment \pm 2 mm
- ▶ Steel nickel plated

Hole line distance LR mm	Order no. / Distance D mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 060	9 075 061	9 075 062	9 075 063	50 ea.
37	9 071 645	9 071 646	9 071 647	9 071 648	200 ea.