



M-66

VALVE & BOX LOCATOR METAL DETECTOR



Fishers M-66 Valve and Box Locator is designed specially for finding buried or paved over valves, box's or vaults. In addition, the M-66 locates survey markers, water or gas meters, conduit, manholes and any other concealed metallic object.

The M-66 detects all metals including aluminum, brass, copper, iron, nickel, steel or tin. Combining sensitivity and accuracy with maximum ground penetration, the M-66 eliminates any guesswork when pinpointing hidden metallic objects.

The electronic balance of the M-66 is easily and quickly tuned for detection within seconds while also allowing for maximum audio and visual indications.

In the Fisher tradition, the M-66 is affordable, tough, and simple to use while providing maximum performance. A two year limited warranty comes standard with the unit.

Features

- Simple operation - only 2 knobs
- Ultra-sensitivity and maximum penetration through soil, asphalt or concrete
- Ground rejection VLF (very low frequency) eliminates false signals
- Detects all metals
- Built-in battery test
- Analog meter and audio target signal
- Adjustable shaft
- Fully submersable 8 inch search coil
- Weather resistant design



200 W. Willmott Rd., Los Banos, CA 93635-5501

T 209.826.3292 F 209.826.0416 www.fisherlab.com info@fisherlab.com

Fisher Labs has been serving the demanding needs of the utility industry with innovative locating solutions - Since 1931. From pipe & cable locators, valve & box locators, sound & leak detectors to water level indicators, Find it... with Fisher!





M-66 specifications

Specifications subject to change without notice.



M-66

- Search Loop ConfigurationDouble D (direct wired)
- Output Frequency of Loop.....4.5kHz,
- Output IndicationSpeaker 16 ohm impedance
.....Audio fequency 450 Hz
- Power Supply9V, each
- Power Consumption.....(-9V) 17 mA
.....(+9V) 4mA min, 6 mA sound
.....threshold, 125 mA max sound
- Weight with 8" coil4.25 lbs.
- Operating Temp.....-4° to +158°F (-20° to +70°C)
.....search loop immersible in water
- DimensionsLength 28" to 48" adjustable
.....(71cm to 122 cm)
- Shipping Weight.....7 lbs.
- Shipping Dimensions.....34.75" x 12.75" x 5.25"
.....(88.3 x 32.4 x 13.3cm)



2-Year Warranty

Fisher warrants the M-101 to be free of defects in materials and workmanship when it is shipped from the factory. The terms of this warranty are fully explained in a warranty registration card that accompanies the instrument. Complete factory and field service facilities support the warranty.

*Warranty may vary outside the U.S. See your distributor for details.

Ordering Information

US & Canadian Customers Contact:

FISHER LABS

200 W. Willmott Rd., Los Banos, CA 93635-5501
T 209.826.3292 F 209.826.0416 info@fisherlab.com
www.fisherlab.com

All Other Countries Contact:

Fisher Export Department

280 State Street, Suite 202, North Haven, CT 06473 USA,
T 203.230.4130 F 203.248.8093
email: fisher@exportdept.com



FRL#8700006-B

