P12000 Propane Heater



Fuel Consumption Low High	5.5hrs/1lb 4hrs/1lb
Heat Output Low High	4000 BTU 5500 BTU
Width Depth Height Backplate Weight	10" 7.25" 16" 9.875" x 0.65" x 23" 25lbs (11.5Kg)

dickin/on MARINE

- 100% Marine Grade Stainless Steel
- Direct Vent Uses No Inside Air
- Glass Viewing Window
- Low Fuel Consumption
- Comes with Chimney, Cap & Backplate
- 12v Circulation Fan (Also 24v & 32v)
- Heats 1100 Cubic ft (12' x 12' x 8')

Installation Parts

Two Stage Regulator	19-162
Single Stage Regulator	19-151
Disposable Bottle Kit	19-150
10ft Propane Hose	19-100-10
20ft Propane Hose	19-100-20
Solenoid	19-153
Gas Alarm w/ Sniffer	19-154
10" Chimney Extension	19-005
28" Chimney Extension	19-000
18" Flue Guard	19-030
Cap Guard	19-080A
Weather Guard (for use w 19-080A)	19-210A
Weather Guard (Cap Only)	19-200A

The Newport P12000 propane heater boasts a higher output rating than it's smaller cousin but still has the low fuel consumption. The direct vent design ensures none of the traditional moisture build up associated with propane heating and allows the heater to use outside air for combustion instead of interior air to keep oxygen levels steady with no worry of oxygen depletion. The P12000 will consistently put out a good amount of dry heat to keep your small space warm and toasty.

The P12000 propane heater comes with one 28" length of flexible chimney to allow you to accomplish installations in tight spaces. The maximum length of the chimney is 56" Also while we recommend a straight installation if possible, the flexible venting allows for a horizontal exit. Included as well is a cap that doubles as a through deck fitting. The cap comes complete with a thick rubber gasket for a water tight seal and a stainless steel dress ring for the interior of your boat.