

Front Adjustable Track Bar

Dodge Ram | 2019 3500 4WD Pickup | 2019 2500 4WD Pickup

Part #: 122324 Rev. 101819



491 W. Garfield Ave., Coldwater, MI 49036 • Phone: 517-279-2135

Web: www.bds-suspension.com • E-mail: tech-bds@ridefox.com

SAFETY WARNING

BDS Suspension Co. recommends this system be installed by a professional technician. In addition to these instructions, professional knowledge of disassembly/ reassembly procedures and post installation checks must be known.

INSTALLATION INSTRUCTIONS

1. Park vehicle on clean flat and level surface. Block the rear wheels for safety.
2. Remove the factory trackbar, retain hardware for installation of new trackbar.
3. Lightly grease and install bushings and sleeves into the trackbar.
4. Adjust trackbar length to stock length for stock height applications, adjust to 39-1/8" for 3" of lift.
5. Install trackbar with the gussets on the 'bottom' side with factory hardware, loc-tite the threads.
6. Adjust length of trackbar to center axle.
7. Tighten trackbar axle hardware to 285 ft-lbs and frame hardware to 74 ft-lbs plus 160deg of rotation
8. Remove the 4 allen bolts and apply loc-tite to the threads, reinstall into trackbar.
9. Install and tighten pinch bolts on trackbar until the collar is un-

Bill of Materials		
Part #	Qty	Description
A350	1	Adjustable Track Bar Assembly
3565	4	Bushing
143	2	1.125 x 18mm ID x 1.622
	1	Loc-Tite

able to be rotated, this should be no more than 40 ft-lbs max.

10. Adjust drag link length to get the steering wheel to be centered. Ensure there is proper engagement of threads. Do not drive the vehicle for extended periods of time with the steering wheel crooked.
11. Recheck all hardware, check again at regular maintenance intervals.

