



TITLE	
AQUACUBE.5625-4320.UN	
DRAWN BY	DATE
J. Ellison	16/10/2023
CUSTOMER	
CUSTOMER	

NOTE:	
All tanks must be fully supported on a flat level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.	
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	

DESCRIPTION:	
CUCOMP.5625-4320.UN Combination Unit c/w single access door and access manway to wet compartment	
ALL DIMENSIONS IN MM - DO NOT SCALE	

DATE	VERSION	NOTES
16/10/2023	A	FIRST ISSUE

TANK SPECIFICATION :	
WET COMPARTMENT	1920 x 1500 x 1500mm
DRY COMPARTMENT	560 x 1500 x 1500mm
EXTERNAL DIMENSIONS	2702 x 2202 x 1618mm
NOMINAL CAPACITY	4320 Litres
INSULATION THICKNESS	25mm
MATERIAL	GRP

SCALE:1:35 SHEET 1 OF 1