# SAFETY DATA SHEET

#### Section 1: Identification

Product Name: OP Ceramic Detailer Product Code: 4140 Product Class: Exterior Finish Coaling Manufacturer/Supplier: Owners Pride 4859 S. 136th Street Omaha, NE 68137 Date Prepared: Date of Review/Update: December 27, 2016 May 2, 2017

# Section 2: Hazard Identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

800-424-9300

Telephone: 402-715-9749

Emergency Telephone: CHEM TREC

GHS Hazard Symbols:

GHS Classification: Signal Word: Skin Corrosion/Irritation Category 3; Eye Damage/Irritation Category 2B Warning

<u>GHS Hazard Statements:</u> H316 Causes mild skin irritation H320 Causes eye irritation

GHS Precautionary Statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash hands thoroughly after handling.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332 + P313 If skin irritation occurs: Get medical advice/attention.

P337+ P313 If eye irritation persists: Get medical advice/attention.

#### Signs and Symptoms of Exposure:

| Eye:   | Irritation including tearing or redness.  |        |               |                        |  |  |  |
|--|---|--------|---------------|------------------------|--|--|--|
| Skin:  | Prolonged skin contact may cause irritation including redness, irritation, itching. |        |               |                        |  |  |  |
| Ingestion:   | May cause gastrointestinal irritation   |        |               |                        |  |  |  |
| Inhalation:  | None are known  |        |               |                        |  |  |  |
| Medical Conditions Aggravated by Exposure: None known. |   |        |               |                        |  |  |  |
| HMIS Rating:   | Health- 1   | Fire-0 | Reactivity- 0 | Personal Protection- C |  |  |  |

### Section 3: Composition/Information on Ingredients

| Chemical Name           | CAS Number  | % Range | OSHA PEL        | ACGHI TLV       |
|-------------------------|-------------|---------|-----------------|-----------------|
| Isopropyl Alcohol       | 67-63-1     | 1-5     | TWA 400ppm      | TWA 200ppm      |
| Silicone Micro-Emulsion | Proprietary | 1-5     | Not Established | Not Established |

#### Section 4: First Aid Measures

 Eye Contact:
 Flush with large amounts of water for 15 minutes. If symptoms persist, seek medical attention.

 Skin Contact:
 Wash affected area with water for 15 minutes. Remove contaminated clothing and launder before reuse.

 Ingestion:
 Never give anything by mouth to an unconscious person. If person is conscious then give several glasses of water. Do not induce vomiting. Keep warm and quiet. Seek medical attention.

 Inhalation:
 Remove from exposure. Seek fresh air. Keep warm and quiet. If symptoms persist seek medical attention.

### Section 5: Fire-Fighting Measures

Fire and Explosive Properlies: Flash Point: >140°F / TCC Flammable Limits: LEL / UEL: No Data Exlinguishing Media: Water fog, dry chemicals or carbon dioxide. Special Fire Fighting Procedures: Full protective equipment including self contained breathing apparatus for confined areas. Unusual Fire and Explosion Hazards: None are known

#### Section 6: Accidental Release Measures

Steps to be taken if Material is Spilled or Leaked:. Contain spill. Ventilate and remove with inert absorbent.

#### Section 7: Handling and Storage

Precautions to be taken in Handling and Storage:

Never wear oil soaked clothing. Launder or dry-clean before wearing. Affix proper warning labels on containers in accordance with 29CFR 1010.1200.

#### Section 8: Exposure Controls and Personal Protection

Ventilation: Use only with adequate ventilation. Avoid breathing vapor or mist. Local exhaust preferred. Respirator Protection: Properly fitted NIOSH/MSHA approved respirator for ingredients found in SECTION 3 if TLV is exceeded. Gloves rated for protection against ingredients in SECTION 3. Skin Protection: Eye Protection: Safety glasses with side shields or chemical goggles.

None

#### Section 9: Physical and Chemical Properties

**Boiling Point:** 212'F Vapor Densily: Unknown Specific Gravity:  $1.01 \pm 0.05$ % Volatile:  $95.0 \pm 0.5$ Appearance/Odor: Pink Liquid, Tropical Odor.

#### Section 10: Stability and Reactivity

Stability: Stable Materials to Avoid: Strong oxidizers Hazardous Polymerization: Will not occur. Conditions to Avoid: Open flames, sources of ignition. Hazardous Decomposition Products: Various hydrocarbons of incomplete combustion.

### Section 11: Toxicology Information

IARC, NTP, OSHA Carcinogen:

# Section 12: Ecological Information

No data

# Section 13: Disposal Considerations

Waste Disposal: Dispose of in accordance with federal, state, and local regulations.

#### Section 14: Transport Information

D.O.T. REQUIREMENTS (49CFR 172.101): Not regulated by D.O.T.

#### Section 15: Regulatory Information

|   | RQ (REPORTABLE QUAN     | ITITY) 49CFR 172.     | .101:         | None  |                 |  |
|---|-------------------------|-----------------------|---------------|---|-----------------|--|
| TSCA (Toxic Substances Control Act) Status: |                         |                       |               | The intentional ingredients of this product are listed. |                 |  |
|   | CERCLA RQ - 40CFR 302   | .4:                   |               | None  |                 |  |
|   | SARA 302 COMPONENTS     | 3 - 40CFR 355 App     | endix A:      | None  |                 |  |
|   | SECTION 311/312 HAZAF   | RD CLASS - 40CFF      | R 370.2       |   |                 |  |
|   | Immediate               | (X)                   |               | Reactive  | ()              |  |
|   | Delayed                 | ()                    |               | Sudden Release of Pressure                              | 0               |  |
|   | Fire                    | ()                    |               |   |                 |  |
|   | SARA 313 COMPONENTS     | S - 40CFR 372.65:     |               | None  |                 |  |
| 1   | WORKPLACE HAZARDO       | <b>US INFORMATION</b> | SYSTEM (WHM   | <u>/IS)</u>   |                 |  |
|   | Ingredient              |                       | Max. % By Wt. | <u>LD50</u>   | <u>LC50</u>     |  |
|   | Isopropyl Alcohol       | 67-63-1               | 1 - 5         | 5000 mg/kg  | 45248 ppm       |  |
|   | Silicone Micro-Emulsion |                       | 1-5           | Not established   | Not established |  |
|   |                         |                       |               |   |                 |  |
|   |                         |                       |               |   |                 |  |

**CALIFORNIA PROPOSITION 65:** 

None

Vapor Pressure (mmHg @ 68°F): Solubility in Water: Melting Point: pH:

Unknown Complete Not Applicable Not Applicable

Page 2 of 3

 $\sim c$ 

·. '.

. .

. 1

, .<sup>.</sup>.

٠

Section 16: Other Information Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.

· · . .

• • • •

\*. \*t..

٠.

. . . . . . . . .

1.00

۰.

۰.

•

., X

, •••

"i· · ·

ч. т. .

. •