

# SAFETY DATA SHEET

## Section 1: Identification

Product Name: Ceramic Coating  
Product Code: OPC7  
Product Class: Exterior Finish Coating  
Manufacturer/Supplier: Owners Pride  
13730 P St.  
Omaha, Nebraska 68137  
Telephone: 402-715-9749  
Emergency Telephone: CHEMTREC 800-424-9300

Date Prepared: December 1, 2021  
Date of Review/Update:

## Section 2: Hazard Identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

### GHS Hazard Symbols:



**GHS Classification:** Flammable Liquid Category 3; Toxic to reproduction Category 2; Skin irritation Category 2; Specific target organ toxicity-single exposure Category 3; Aspiration Hazard Category 1; Acute Toxicity inhalation Category 4

**Signal Word:** Danger

### GHS Hazard Statements:

H226 Flammable liquid and vapor.  
H361 Suspected of damaging fertility.  
H332 Harmful if inhaled.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.

### GHS Precautionary Statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ eye protection/ face protection.

### Signs and Symptoms of Exposure:

Eye: Irritation including tearing or redness.  
Skin: Prolonged skin contact may cause irritation including redness, irritation, itching.  
Ingestion: May cause gastrointestinal irritation  
Inhalation: None are known  
Medical Conditions Aggravated by Exposure: None known.  
HMIS Rating: Health- 1 Fire- 3 Reactivity- 0 Personal Protection- C

## Section 3: Composition/Information on Ingredients

Chemical Name	CAS Number	% Range	OSHA PEL	ACGHI TLV
Silane Blend	Proprietary	10-40		
Naphtha (petroleum), heavy alkylate	64741-65-7	40-75		

## Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.  
Skin Contact: Wash with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Destroy or thoroughly clean contaminated shoes.  
Ingestion: Never give anything by mouth to an unconscious person. If person is conscious then give several glasses of water. Do not induce vomiting. Keep warm and quiet. Seek medical attention.  
Inhalation: Move to fresh air. Treat symptomatically. Get medical attention if symptoms persist,

## **Section 5: Fire-Fighting Measures**

General fire hazards: Flammable liquid and vapor. USE WATER WITH CAUTION. Material will float and may ignite on surface of water. Use water spray to keep fire-exposed containers cool.

Fire and Explosive Properties: Flash Point: 44°C / TCC Flammable Limits: LEL / UEL: No Data

Extinguishing Media: Water spray, dry chemical, carbon dioxide, alcohol foam

Special hazards arising from the substance: Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations.

Special Fire Fighting Procedures: Full protective equipment including self contained breathing apparatus for confined areas. Water may be ineffective in fighting the fire. Use water spray to keep fire exposed containers cool.

## **Section 6: Accidental Release Measures**

Steps to be taken if Material is Spilled or Leaked: Eliminate the sources of ignition. Absorb spills with vermiculite or other inert material, then place in a container for chemical waste. Larger spills use water spray to disperse vapors and dilute spill to a non-flammable mixture. Prevent any runoff from entering any drains, sewers or streams. Dike for later disposal.

Notification procedures: in the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

## **Section 7: Handling and Storage**

Precautions to be taken in Handling and Storage:

Avoid breathing mist or vapors. Avoid contact with eyes and prolonged or repeated contact with skin. Use only with adequate ventilation. Wash hands thoroughly after handling. Keep container tightly closed and in a well-ventilated place. Affix proper warning labels on containers in accordance with 29CFR 1010.1200.

## **Section 8: Exposure Controls and Personal Protection**

Ventilation: Use only with adequate ventilation. Avoid breathing vapor or mist. Local exhaust preferred.

Respirator Protection: Properly fitted NIOSH/MSHA approved respirator for ingredients found in SECTION 3 if TLV is exceeded.

Skin Protection: Gloves rated for protection against ingredients in SECTION 3.

Eye Protection: Safety glasses with side shields or chemical goggles.

## **Section 9: Physical and Chemical Properties**

Boiling Point: 160°C

Vapor Density: 5 (air=1)

Specific Gravity: 0.82 ± 0.05

Appearance/Odor: Clear liquid, mild Spearmint odor

Vapor Pressure (mmHg @ 68°F): Unknown

Solubility in Water: Not Soluble

Melting Point: Not Applicable

pH: Not Applicable

## **Section 10: Stability and Reactivity**

Stability: Stable

Hazardous Polymerization: Will not occur.

Hazardous Decomposition Products: Various hydrocarbons of incomplete combustion.

Materials to Avoid: Strong oxidizers

Conditions to Avoid: Open flames, sources of ignition.

## **Section 11: Toxicology Information**

IARC, NTP, OSHA Carcinogen: None

Information on likely routes of exposure:

Inhalation: may cause drowsiness or dizziness

Ingestion: none known

Skin contact: prolonged or repeated skin contact may cause drying, cracking, or irritation

Eye contact: causes serious eye irritation

Information on toxicological effects:

Acute Toxicity

Oral product: oral LD-50: rat; 6750 mg/kg

Dermal product: dermal LD-50: rat; >20 ml/kg

Inhalation product: LC50: rat; 8h: 50.6 mg/l

Repeated dose toxicity product: noael: rat, oral study, 90 days: 90 mg/kg

Skin corrosion/irritation product: guinea pig, 4h: slight

Respiratory or skin sensitization product: skin sensitization: guinea pig: non-sensitizing

## **Section 12: Ecological Information**

All work practices must be aimed at eliminating environmental contamination.

Effects of material on plants and animals: This product may be harmful or fatal to plants and animal life if released into the environment.

Effect of material on aquatic life: The most sensitive known aquatic group to any component of this product is: Fish: LC-50 (golden orfe, 48h): 265-360 mg/l

Keep out of sewers and natural water supplies. This material is a mobile liquid.

