



Glass, Ceramic & Mirror Decontaminant/Cleaner

Presentation, datasheet and operating instructions

Product Description: NanoProtection Glass & Ceramic Cleaner is a highly effective cleanser with abrasive agents. The product is used for the final preparation of the surfaces that will be treated later with Nano processing products. Measured and adapted for each surface (except marble) in order to achieve the best possible adhesion and durability of the treatment, Glass & Ceramic Cleaner Allows optimum preparation of surfaces prior to application of most treatments (except plastic).

Agents: Rare earth metal oxides in water.

Smell: Without.

Color: Yellow/brown.

Ph: 6-8.

Use:

Application Conditions: Apply the product at temperatures between + 5 °c and + 30 °c.

Do not treat in direct sunlight. Treat in small areas if temperatures are at 30 °c. Do not treat in Below 0 °c.

The product must be applied under conditions of air humidity and temperature Normal.

Surface Preparation: The surface must be free of all coarse and visible pollution, such as Impurities, traces of limestone and dirt.

Tips for use: Shake well before use. Apply Glass & Ceramic Cleaner On a Sponge and then clean the surface with circular movements. Let the product dry 1-2 minutes (appearance of a white veil), then using a lint-free cloth, polish the surface to eliminate all residual of dry product. Once the surface has been cleaned, do not touch it with your fingers or make it come in contact with Water if a nano treatment is going to be applied.

Do not apply with chlorinated products, this can produce harmful fumes. Do not use on Acid-sensitive surfaces such as marble or other stones, or plastic or acrylic surfaces, this can cause scratches.

Amount of Use: Approx. 10-20ml/m²

Drying Time: With temperatures of 30 °c, the product dries rapidly (approx. 30 sec.).

Conservation: Storage for one year in its original packaging without opening. Store in a Place between + 5 °c and + 25 °c. Store away from solar radiation. Close the opened containers well.

Hazardous Products Regulations: Glass & Ceramic Cleaner is not subject to The reporting requirement under the hazardous products regulations. For further information please also consult our Safety data sheet. These implementation recommendations are based on our experience and extensive work Search, however, they do not release the user from testing the product before an application. NanoProtection guarantees the quality of its products but expressly disclaims all liability in case of Non-compliance by the user with the recommendations and conditions of use of the said products, in particular but Not exclusively in case of failure to apply, application by unqualified personnel, use of Products not compatible with the company's products NanoProtection or bad conditions Weather.

Protection Nano Inc – Head Office, Saint Eustache, Qc Canada

Info@nanoprotection.ca – www.nanoprotection.ca

SAC: 1-866-472-5296 - CEO: 514-893-5296



Waterproof Joints Treatment

Product Summary: NanoProtection JOINTS is a nanotechnology-based product designed to impart hydrophobic and oleophobic properties to mineral tile joints. It prevents water infiltration, reduces dirt adhesion, fights fouling of joints, and extends the life of seals.

Features: High hydrophobicity (contact angle >120°) | Strong anti-adherent properties
Excellent "easy to clean" effect, especially against air pollutants | Solvent-free and odorless
Resists high-pressure wash (50-60 bars) | UV-stable and abrasion-resistant
Withstands high temperatures and freeze/thaw cycles | Prevents contamination and moss/mushroom growth | Extended service life with less cleaning

Usage: Apply at temperatures between +5°C and +30°C, avoiding direct sunlight. Ensure the surface is clean and dry.

Surface Preparation: Clean the joint of visible dirt.

Application: Shake well before use and wear gloves. After pre-cleaning, ensure the joint is dry. Apply NanoProtection JOINTS uniformly with a brush until saturated. Wipe off any product that spills onto the tiles. Avoid contact with water or cleaning agents during drying. Full drying takes 24 hours.

Maintenance: The hydrophobic effect can be tested before 24 hours (water should bead), while the "easy to clean" effect can only be tested after 24 hours (do not rub the surface during this time).

Amount of Use: Approximately 20ml of product per 1m² of full joint, depending on its porosity.

Longevity: The treatment is active for several years due to deep penetration.

Advantages: Permanence and Durability: UV stability ensures long-lasting functionality.

Abrasion resistance/Easy to clean effect: A permanent chemical bond provides excellent abrasion resistance | Chemical Stability: Resistant to most household and industrial cleaners (except concentrated alkaline solutions).

Storage: Store unopened for 2 years in its original packaging at temperatures between +5°C and +25°C, away from sunlight. Seal opened containers tightly.