



240 Volts

Refer to page 3 for installation under soft surfaces.

Model	Length		Spacing (ft ²)		Power Output			Guides
	ft.	m.	3" 14,8 W	ARDEX FLEXBONE, PROVAHEAT 4" 11,1 W	Watt	Amp	Ohms	
3,7GCWC-240V-10	33,0	10,1	8,3	11,0	120	0,5	480,0	10
3,7GCWC-240V-14	49,5	15,1	12,4	16,5	180	0,8	320,0	15
3,7GCWC-240V-19	66,0	20,2	16,5	22,0	240	1,0	240,0	20
3,7GCWC-240V-24	82,5	25,1	20,6	27,5	300	1,3	192,0	20
3,7GCWC-240V-29	99,0	30,2	24,8	33,0	360	1,5	160,0	20
3,7GCWC-240V-34	115,5	35,2	28,9	38,5	420	1,8	137,1	30
3,7GCWC-240V-38	132,0	40,2	33,0	44,0	480	2,0	120,0	30
3,7GCWC-240V-43	148,5	45,3	37,1	49,5	540	2,3	106,7	30
3,7GCWC-240V-48	165,0	50,2	41,3	55,0	600	2,5	96,0	40
3,7GCWC-240V-53	175,0	53,3	43,8	58,3	650	2,7	88,6	40
3,7GCWC-240V-58	198,0	60,4	49,5	66,0	720	3,0	80,0	40
3,7GCWC-240V-63	208,0	63,4	52,0	69,3	770	3,2	74,8	50
3,7GCWC-240V-67	231,0	70,4	57,8	77,0	840	3,5	68,6	50
3,7GCWC-240V-72	238,0	72,5	59,5	79,3	880	3,7	65,5	50
3,7GCWC-240V-77	264,0	80,4	66,0	88,0	960	4,0	60,0	50
3,7GCWC-240V-82	271,0	82,6	67,8	90,3	1000	4,2	57,6	60
3,7GCWC-240V-87	297,0	90,6	74,3	99,0	1080	4,5	53,3	60
3,7GCWC-240V-96	330,0	100,6	82,5	110,0	1200	5,0	48,0	60
3,7GCWC-240V-106	363,0	110,6	90,8	121,0	1320	5,5	43,6	60
3,7GCWC-240V-115	396,0	120,8	99,0	132,0	1440	6,0	40,0	70
3,7GCWC-240V-126	429,0	130,8	107,3	143,0	1560	6,5	36,9	70
3,7GCWC-240V-135	462,0	140,8	115,5	154,0	1680	7,0	34,3	80
3,7GCWC-240V-145	479,0	146,0	119,8	159,7	1770	7,4	32,5	80
3,7GCWC-240V-154	528,0	161,0	132,0	176,0	1920	8,0	30,0	80
3,7GCWC-240V-173	594,0	181,0	148,5	198,0	2160	9,0	26,7	90
3,7GCWC-240V-192	660,0	201,2	165,0	220,0	2400	10,0	24,0	90
3,7GCWC-240V-212	726,0	221,2	181,5	242,0	2640	11,0	21,8	90
3,7GCWC-240V-231	792,0	241,4	198,0	264,0	2880	12,0	20,0	100
3,7GCWC-240V-250	858,0	261,5	214,5	286,0	3120	13,0	18,5	100
3,7GCWC-240V-270	924,0	281,6	231,0	308,0	3360	14,0	17,1	110
3,7GCWC-240V-289	990,0	301,8	247,5	330,0	3600	15,0	16,0	110

CND prices subject to change without notice.

Includes cable, one floor sensor and plastic cable guides.