

# **PC Console Setup**

Download and Unzip the PC Client Console software provided by BridgeCom Systems. The file is located at the following link: http://bridgecomsystems.com/Support.html

Once downloaded, install the file by clicking on the exe file.

#### To Run the Console Program

a) From windows desktop click 'Start', 'All Programs'b) Click 'RnPc'

#### Setup

The console client will default to a 2-channel console and will appear as follows:



You can change the number of visible channels by selecting Edit and then adjusting the pre-built skin to the required number of channels. Experiment with this to your liking. For the rest of this setup tutorial we will use a pre-built skin of 4 channels positioned vertically as shown below:



To start, press Edit and from the drop down menu press Parameter. If this is the first time selecting this setting, enter a Password to use. We recommend using your name.

Enter the password again for verification.

Enter matching password in both boxes 🛛 🔀					
Enter your password here					
Enter password again for verification					
Passwords match					
ОК	Cancel				

### Enter the Common Tab

Setup Site Name on channel one using the following screen shot as a guide.

Parameters 🛛 🔀				
common or	ne channe	Ŋ		
		Site name	rons-desk	
		Talk activation O Hold for talk	⊙ Click on, click off	
۵	AGC	Enable	AGC level	40
Micropho	one boost	100	🗧 🛛 Speaker b	oost 100
	🛃 All so	und devices		Console features
		Ratio Select/Unsele	ct 50	•
		Maximum # channe	ls 20	•
	Permane	ent warning on fixed		Reset password
	ок		Apply	Cancel

Type **YOUR** name in the space like this: rons-desk. This is how the PC Client will be recognized by the TL-NET Server/MV control center.Click 'Apply." Click the "one channel" tab:

Parameters	X
common one channel	
Receive audio	WindowsMultimedia Default
Send audio	WindowsMultimedia Default
Sound buffers 3	Test sound device
Primary server	bridgecom2.dyndns.org
Secondary server	
Cross Patch name	
Enable LTR proceed tone	Volume 90
Courtesy tone blank 💌	Volume 50
Channel Select	
<ul> <li>●1</li> <li>●2</li> <li>●3</li> <li>●4</li> <li>●5</li> <li>●11</li> <li>●12</li> <li>●13</li> <li>●14</li> <li>●1</li> </ul>	06     07     08     09     010       5     016     017     018     019     020
ОК	Apply Cancel

Pick your audio Devices, both receive and send audio If nothing is listed choose Default.

Please set Sound Buffers to 5 (Five)

### Please type in Remote Server: Bridgecom2.dyndns.org

Note: if this is for your own TL-NET server/ MV Control Center, please type in your server address in this space.

Click 'Apply," then Click 'OK' when done.

Note: LTR Courtesy Proceed tones optional. If you prefer to not use a courtesy tone you can select blank. Also, courtesy tones can be different for each channel.



## Main Console Screen:

The Connection LED's should go from Red to Green. You're all set!

You can click the PTT button to key the mic, carry on a conversation. Click PTT again to un-key.

## NOTE:

You will be connected to BridgeCom's Server unless you have mistyped the server name in the set-up, or your PC isn't connected to the ethernet, or you have not selected the proper sound card.

If doing a demo, let BridgeCom Systems know when you are connected and we can perform the demo with you.

Thanks,

BridgeCom Systems, Inc. 617 Liberty Road Smithville, MO 64089 816-532-8451