

# HOSS™ IIIA

**SOFT ARMOR PANELS** Ballistic Specification

REV 1.24

<b>NIJ 0101.06 MODEL #</b>	Hoss IIIA
<b>NIJ 0101.06 THREAT LEVEL</b>	IIIA
<b>NIJ CERTIFICATION SIZES</b>	C1 - C5
<b>BALLISTIC MATERIAL</b>	100% Woven Aramid
<b>WEIGHT</b>	1.55 psf
<b>THINNESS</b>	.35 in (8.89mm)
<b>V50 - 357sig 125gr TMJ (new)</b>	1749 ft/s (533m/s)
<b>V50 - 357sig 125gr TMJ (conditioned)</b>	1781 ft/s (543m/s)
<b>P-BFS Avg. - 357sig 125gr TMJ</b>	26 mm
<b>V50 - 44mag 240gr JHP (new)</b>	1585 ft/s (483m/s)
<b>V50 - 44mag 240gr JHP (conditioned)</b>	1677 ft/s (511m/s)
<b>P-BFS Avg. - 44mag 240gr JHP</b>	33.9 mm

## SPECIAL THREAT TESTING

<b>V50 - 2gr RCC</b>	3094 fps (943 m/s)
<b>V50 - 4gr RCC</b>	2746 fps (837 m/s)
<b>V50 - 16gr RCC</b>	2273 fps (693 m/s)
<b>V50 - 17gr FSP (.22cal)</b>	2104 fps (641 m/s)
<b>V50 - 64gr RCC</b>	1900 fps (579 m/s)

### WARBIRD PROTECTION GROUP, INC.

333 W. Grandview Parkway, Suite 200  
Traverse City, MI 49684  
(231) 645-7283



warbirdpro.com