

## product specification

www.oriel-lighting.com.au

## 10W PROTON LED 3000K Black

SKU:LF3613BK

The powerful and efficient PROTON LED recessed light sits flush along your ceiling and is supplied with a flex-and-plug for easy installation. Dimmable with most LED friendly dimmers. Ideal for use in many applications, the Proton is available in white or black, in three colour temperatures, to suit your preference. CA90 insulation rating - abutted only.

## Additional information



BrandLighting FactoryColourBLACKGlobe TypeINTEGRALLEDMax. Wattage10wVoltage240VVoltageD120 C90 Rec80Fitting DiameterD120D120C90 Rec80Fitting CutoutC90Fitting RecessR80Light SourceSMD LEDColour Temperature3000KColour Temperature1944In PatingIP44Light SourceC490Light SourceC490Light SourceL941Supplier CodeL9513BK		
Globe TypeINTEGRALLEDMax. Watage10wVoltage240VItem DimensionsD120 C90 Rec80Item DimensionsD120Fitting DiameterD120Colour Fitting RecessR80Lumen OutputStolmColour Temperature3000KColour Rendition (CR)>Ra82IP RatingIP44Colour SentingCaseColour Rendition (CR)CaseColour Renditio	Brand	Lighting Factory
Max. Wattage10wVoltage240VItem DimensionsD120 C90 Rec80Fitting DiameterD120Fitting CutoutC90Fitting RecessR80Light SourceSMD LEDLumen Output850ImColour Temperature3000KI P RatingIP44IC RatingCA90	Colour	BLACK
Voitage240VItem DimensionsD120 C90 Rec80Fitting DiameterD120D120C90Fitting CutoutC90Fitting RecessR80Light SourceSMD LEDLumen Output850ImColour Temperature3000KColour Rendition (CRI)>Ra82IP RatingIP44Colour Rendition (CRI)CA90	Globe Type	INTEGRAL.LED
Item DimensionsD120 C90 Rec80Fitting DiameterD120Fitting CutoutC90Fitting RecessR80Light SourceSMD LEDColour Temperature3000KColour Rendition (CRI)>Ra82IP RatingIP44CA90	Max. Wattage	10w
Fitting DiameterD120Fitting CutoutC90Fitting RecessR80Light SourceSMD LEDColour Temperature3000KColour Rendition (CRI)>Ra82IP RatingIP44Colour LatingColour Calour Cal	Voltage	240V
Fitting CutoutC90Fitting RecessR80Light SourceSMD LEDLumen Output850lmColour Temperature3000KIn RatingIP44Ic RatingCA90	Item Dimensions	D120 C90 Rec80
Fitting Recess R80   Light Source SMD LED   Lumen Output 850lm   Colour Temperature 3000K   IP Rating IP44   IC Rating CA90	Fitting Diameter	D120
Light Source SMD LED   Lumen Output 850lm   Colour Temperature 3000K   Colour Rendition (CRI) >Ra82   IP Rating IP44   IC Rating CA90	Fitting Cutout	C90
Lumen Output 850lm   Colour Temperature 3000K   Colour Rendition (CRI) >Ra82   IP Rating IP44   IC Rating CA90	Fitting Recess	R80
Colour Temperature   3000K     Colour Rendition (CRI)   >Ra82     IP Rating   IP44     IC Rating   CA90	Light Source	SMD LED
Colour Rendition (CRI) >Ra82   IP Rating IP44   IC Rating CA90	Lumen Output	850lm
IP Rating IP44   IC Rating CA90	Colour Temperature	3000K
IC Rating CA90	Colour Rendition (CRI)	>Ra82
	IP Rating	IP44
Supplier Code LF3613BK	IC Rating	CA90
	Supplier Code	LF3613BK

UPI	9324879214575	
Electrician To Install	This fitting should be installed by a licenced electrician	
Warranty / Guarantee	12 Month Replacement Guarantee	

Unless stated, fittings do not include globes (bulbs). No representations are made as to the suitability of this product for your application. All fixed lights (other than DIY lights) should be installed by a licensed electrical contractor. Due to continuing product development, some specifications may change over time. Refer to our detailed Terms and Conditions, online at: www.oriel-lighting.com.au | Details and specifications are current at the time of printing, and with constant product development, subject to change.

(c) Oriel Lighting



quality lighting at affordable prices | specifications subject to change without notice - check the website for the latest information | www.oriel-lighting.com.au