

Model: AIRSLATE BOMBAY

Codes: 100242667

Group: G-238

Format: 250X120X0,2-0,4CM

Thickness range: {VAL}2-4 mm



## RECOMMENDATIONS

Recommended adhesive	100217753 POLITECH PREMIUM COMPUESTO A + B 10KG	
Recommended joint	100236833 COLORSTUK RAPID CARAMELO N 5KG	
Recommended joint (wet area)	100236833 COLORSTUK RAPID CARAMELO N 5KG	100086920 FILA FOB XTREME 1L
Recommended adhesive (wet area)	100217753 POLITECH PREMIUM COMPUESTO A + B 10KG	

## LABORATORY TESTS

Bulk density	1450 Kg/m3	UNE EN 1936:2007*
Water absorption at atmospheric pressure	1.00%	UNE-EN 13755:2008*
Flammability	C-S2, d0	UNE-EN 13501-1:2007+A1:2010*
Frost resistance	93.1 MPa	UNE-EN 12371:2010*
Resistance to thermal shock	T2	UNE -EN 16140:2011*
Flame-spread or surface characteristics	CLASE II	ASTM E 84*
Coefficient of linear thermal expansion	23 1/(10E6*K)	UNE-EN 10545-8*
Flexural strength	102.2 MPA	EN 12372*

## FEATURES



Protection that reduces the appearance of the most common domestic bacteria.



There are considerable color changes between pieces.



Material from an Asian country.



Material suitable for use on indoor walls.



Gloss-free



Material suitable for use on outdoor walls.



Material suitable for use on shower walls.



Material that stands out for having an asymmetrical surface.

## PACKING

Sales units per box	15 M2/BOX	
Sales units per pallet	375 M2/PAL	
Sales units per unit	3 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Net weight	4.513333 KG/M2	
Gross weight	4.646667 KG/M2	

