

Model: AIRSLATE DELHI

Codes: 100242689

Group: G-238

Format: 250X120X0,2-0,4CM

Thickness range: {VAL}2-4 mm









RECOMMENDATIONS

Recommended adhesive	100217753 POLITECH PREMIUM COMPUESTO A + B 10KG	
Recommended joint	100236449 COLORSTUK RAPID CEMENTO N 5KG	
Recommended joint (wet area)	100236449 COLORSTUK RAPID CEMENTO N 5KG	100086920 FILA FOB XTREME 1L
Recommended adhesive (wet area)	100217753 POLITECH PREMIUM COMPUESTO A + B 10KG	

LABORATORY TESTS

Bulk density	1450 Kg/m3	UNE EN 1936:2007*
Water absorption at atmospheric pressure	1.00%	UNE-EN 13755:2008*
Flammability	C-S2, d0	UNE-EN 13501-1:2007+A1:2010*
Frost resistance	93.1 MPa	UNE-EN 12371:2010*
Resistance to thermal shock	T2	UNE -EN 16140:2011*
Flame-spread or surface characteristics	CLASE II	ASTM E 84*
Coefficient of linear thermal expansion	23 1/(10E6*K)	UNE-EN 10545-8*
Flexural strength	102.2 MPA	EN 12372*

FEATURES

-  Protection that reduces the appearance of the most common domestic bacteria.
-  Material from an Asian country.
-  Gloss-free
-  Material suitable for use on shower walls.
-  There are considerable color changes between pieces.
-  Material suitable for use on indoor walls.
-  Material suitable for use on outdoor walls.
-  Material that stands out for having an asymmetrical surface.

PACKING

Sales units per box	15 M2/BOX	
Sales units per pallet	375 M2/PAL	
Sales units per unit	3 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Net weight	4.513333 KG/M2	
Gross weight	4.646667 KG/M2	

