

Model: MARMI CHINA 33,3X100(A) Codes: 100292132 Water absorption: BIII - Revestimiento (10%<=E<=20%)



Crazing resistance

Sales units per unit

DIMENSIONAL FEATURES UNE-EN ISO 10545-2			
Thickness	9.3 MM	+/-5%*	
Width	332.8 MM		
Length	1000 MM		
Length and width deviation	Below 0.15%	+/-0.3%*	
Side straightness deviation	Below 0.15%	+/-0.3%*	
Squareness deviation	Below 0.15%	+/-0.3%*	
Surface flatness deviation	Below 0.15%	+/-0.4%*	
*ISO-13006:2018 UNE-EN 14411:2016			
MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11			
Breaking strength	1362 N	>600N*	
Modulus of rupture	25.8 N/MM2	>=12N/mm2*	

*ISO-13006:2018 UNE-EN 14411:2016			
HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995			
Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*	
Stain resistance	Class 5. Easy cleaning with water	3 Min.*	
*ISO-13006:2018 UNE-EN 14411:2016			
SCOPE OF USE			
Technical code-1	Use on walls		
	DACKING		
PACKING			
Sales units per box	1.665002 M2/BOX		
Sales units per pallet	73.260073 M2/PAL		

Resists 3 cycles

0.333 M2/PIECE

System Certification SGS SGS SGS

Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.