L'ANTIC COLONIAL

Model: TOUCH NAVY Codes: 100333142 Group: G-226

Format: 8X30X0,85CM



	RECOMMENDATIONS
Recommended adhesive	100043280 TIXOCEM PLUS 25KG
Recommended joint	100236409 COLORSTUK 0-4 ANTRACITA N 5KG
Recommended joint (wet area)	100236409 COLORSTUK 0-4 ANTRACITA N 5KG
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG

DIMENSIONAL FEATURES				
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*		
Side straightness deviation	±0.3 %	UNE-EN ISO 10545-2*		
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*		
Surface flatness deviation	+0.5 %	LINE-EN ISO 10545-2*		

FEATURES



Material with surface with the ability to produce reflections.



Material suitable for use on shower walls.



Material suitable for use on indoor walls.



There are considerable color changes between pieces.



Material recommended for installation on walls.

PHYSICAL PROPERTIES				
Water absorption	BIII	ISO 10545-2*		
Breaking strength	>900 N	>600N*		
Coefficient of linear thermal expansion	<6.6 1/(10E6*K)			
Crack resistance	PASS	ISO 10545-11*		

CHEMICAL PROPERTIES				
Stain resistance	Clase 5	ISO 10545-14*		
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*		





TOUCH NAVY

L'ANTIC COLONIAL

PACKING				
Sales units per box	0.672 M2/BOX			
Sales units per pallet	67.2 M2/PAL			
Sales units per unit	0.024 M2/PIECE			
Sale unit	M2			
Base unit	ST			
Net weight	14.416667 KG/M2			
Gross weight	14.75 KG/M2			





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

25/01/2024