Model: TOUCH PEARL Codes: 100333150 Group: G-226 Format: 8X30X0,85CM

## L'ANTIC COLONIAL



	RECOMMENDATIONS	
Recommended adhesive	100043280 TIXOCEM PLUS 25KG	
Recommended joint	100236442 COLORSTUK 0-4 BLANCO N 5KG	
Recommended joint (wet area)	100236442 COLORSTUK 0-4 BLANCO N 5KG	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG	
	DIMENSIONAL FEATURES	
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.3 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*
	FEATURES	
	TEATORES	
Material with surface with the ability to produce	reflections Material suitable	for use on shower walls.
Material suitable for use on indoor walls.		rable color changes between pieces.
Material suitable for use on indoor walls.		
Material suitable for use on indoor walls.		
Material suitable for use on indoor walls.	There are conside	
Material suitable for use on indoor walls.	There are conside PHYSICAL PROPERTIES	rable color changes between pieces.
Material suitable for use on indoor walls.	There are conside PHYSICAL PROPERTIES BIII	rable color changes between pieces. ISO 10545-2*
Material suitable for use on indoor walls.	PHYSICAL PROPERTIES BIII >900 N	rable color changes between pieces. ISO 10545-2*
Waterial suitable for use on indoor walls.         Waterial recommended for installation on walls.         Water absorption         Breaking strength         Coefficient of linear thermal expansion	PHYSICAL PROPERTIES  PHYSICAL PROPERTIES  BIII >900 N <6.6.1/(10E6*K) PASS	rable color changes between pieces. ISO 10545-2* >600N*
Waterial suitable for use on indoor walls.         Waterial recommended for installation on walls.         Water absorption         Breaking strength         Coefficient of linear thermal expansion	PHYSICAL PROPERTIES BIII >900 N <6.6 1/(10E6*K)	rable color changes between pieces. ISO 10545-2* >600N*
Waterial suitable for use on indoor walls.         Waterial recommended for installation on walls.         Water absorption         Breaking strength         Coefficient of linear thermal expansion	PHYSICAL PROPERTIES  PHYSICAL PROPERTIES  BIII >900 N <6.6.1/(10E6*K) PASS	rable color changes between pieces. ISO 10545-2* >600N*



25/01/2024

## L'ANTIC COLONIAL

## 100333150 TOUCH PEARL

	PACKING	
Sales units per box	0.672 M2/BOX	
Sales units per pallet	67.2 M2/PAL	
Sales units per unit	0.024 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Net weight	14.541667 KG/M2	
Gross weight	14.875 KG/M2	



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.