## Footnotes

- All shroud panels included.
- Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition.
- This specification can be subject to a variance of (+ or -) 10%. Battery weight not included.
- Battery pack weight 29 lbs.
- Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or 3%. Battery pack is 20 lbs. with 12AH batteries.
- Durable solid plastic.
- Deep cycle (AGM or gel-cell type recommended). 18 AH battery pack weighs 33 lbs.
- 10. Tested in accordance with ANSI/RENSA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 11. Up to 14 miles per charge on 18 AH batteries.
- 12. Battery weight may vary based on manufacturer.
- 13. Width of base (not including seat).
- 14. Does not account for anti-tip clearance
- 15. Includes standard seat weight.
- Requires upgrade to medium or high-back contoured seat; additional charges apply.
- 17. Not available with 3-wheel version
- (maximum dimension 22x20). 18. Battery pack is 19.5 lbs. with 12 AH batteries.









Go-Go Flite







Pride Scooters











Mobility Products Corp.	
- LIVE YOUR BEST -	

Products Corp.	Travel Pro	Go-Go® Ultra X	Go-Go Elite Traveller®	Go-Go Elite Traveller® Plus/PlusHD	Victory® 9	Victory® 9PS	Victory® 10	Celebrity® X	Maxima	Pursuit®	Pursuit® XL	Wrangler® PMV
FRONT TIRES	2" x 8" SOLID	2" x 8" SOLID (3W) 2" x 7" SOLID (4W)	2" x 8" SOLID (3W) 2" x 7" SOLID (4W)	2" x 8" SOLID	3W: 8" SOLID 4W: 9" SOLID	3W: 8" SOLID	3.5" x 10" SOLID	10" SOLID	3" x 10" SOLID	13" SOLID	13" PNEUMATIC	6" x 13"
REAR TIRES	2.5" x 8" SOLID	2.5" x 8" SOLID	2.5" x 8" SOLID	3" x 9" SOLID	2.5" x 9" SOLID	2.5" x 9" SOLID	3.5" x 10" SOLID	10" SOLID	4" x 10" SOLID	13" SOLID	13" PNEUMATIC	6" x 13"
MAXIMUM SPEED <sup>2</sup>	UP TO 4 MPH	UP TO 4 MPH	UP TO 4.25 MPH	UP TO 4.5 MPH	UP TO 5.25 MPH	UP TO 5.5 MPH	UP TO 5.25 MPH	UP TO 6 MPH	UP TO 5.25 MPH	UP TO 7.25 MPH	UP TO 8.25 MPH	UP TO 5/10 MPH
GROUND CLEARANCE <sup>5,14</sup>	1.375″	1.375" (3W) 1.375" (4W)	2.5″	3″	3W: 2" 4W: 2.25"	2" at midframe	3" at midframe	2.25"	3W: 4.25" 4W: 3.25"	3.56″	5.25"	7″
3-W TURNING RADIUS <sup>5</sup>	32.5"	32.5"	32.5"	34.5″	40.25"	41"	42"	41.5"	50.38"	N/A	N/A	N/A
4-W TURNING RADIUS <sup>5</sup>	N/A	44.125"	44.125"	45.75"	51.5"	N/A	54"	54"	54"	67.25"	82.5"	77"
3-W LENGTH/WIDTH <sup>5</sup>	37"/19.5"	37"/19.5"	37"/19.5"	40"/21.125"	43.5"/22.25"	43.5"/23"	45.25"/22.25"	46"/24"	46.5"/28" at armrests	N/A	N/A	N/A
4-W LENGTH/WIDTH <sup>5,13</sup>	N/A	39.75"/19.5"	39.5"/19.5"	40.25"/21.125"	45.5"/22.5"	N/A	47"/22.25"	46.75"/24"	46.875"/25.5" at wheels	53.25"/25.25"	56.25"/27.25"	63"/31"
SEAT-TO-GROUND	20.125"-22.75"	20.125"-22.75"	20.125"-22.75"	3W: 20.5"-22" 4W: 22.75"-23.25"	24.75"-25.75"	23.5"-29.5"	22.25"-24.75"	24.25-25.125"	22"-24"	24.75" - 26.25"	29.75" - 30.75"	27.75"-31.75"
HEIGHT RANGE SEAT TYPE (STANDARD)	COMPACT, FOLDABLE (17"X17")	COMPACT, FOLDABLE (17"X17")	COMPACT, FOLDABLE (17"X17")	COMPACT, FOLDABLE (17"X17")	FOLDABLE, MOLDED PLASTIC (18"X17")	FOLDABLE, MOLDED PLASTIC (18"X17")	FOLDABLE, MOLDED PLASTIC (18"X17")	DELUXE MOLDED PLASTIC W/SLIDERS (19"X16")	DELUXE CONTOURED MEDIUM-BACK (22"X18.5")	DELUXE RECLINING H/B W/ SLIDERS & HEADREST (19"X17")	DELUXE RECLINING H/B W/ SLIDERS & HEADREST (19.5"X17.5")	DX CONTOURED HIGH-BACK WITH ADJ. HEADREST & SLIDERS (18"X16")
MAXIMUM DIMENSIONS	(CALL FOR DETAILS)	(CALL FOR DETAILS)	(CALL FOR DETAILS)	(CALL FOR DETAILS)	(CALL FOR DETAILS)	(CALL FOR DETAILS)	(22" X 22") <sup>16, 17</sup>	(22" X 20") <sup>16</sup>	(22" X 22")	CALL FOR DETAILS	CALL FOR DETAILS	(22" X 22")
(3/4-WHEEL) WEIGHT <sup>3,5,15</sup>	72 LBS.	72 LBS./78.5 LBS.	75 LBS./78.5 LBS.	84 LBS./87 LBS.	117.5 LBS./131 LBS.	131 LBS.	131.5 LBS./132.5 LBS.	141.5 LBS./151 LBS.	171 LBS./189 LBS.	218.5 LBS.	205.5 LBS.	N/A/216 LBS.
SEAT-TO-DECK HEIGHT RANGE	15.75″-17.25″	15.75″-17.25″	15.75″-17.25″	16.25″-17.75″	17.25″-18.75″	17.25″-23.25″	17.5″-19″	16.5″-18.5″	16″-18″	17″-18.25″	27″-28.5″	19″-23″
BATTERY WEIGHT <sup>12</sup>	9 LBS. EA. <sup>18</sup>	9 LBS. EA.6	9 LBS. EA. <sup>6</sup> / 14 LBS. EA. <sup>9</sup>	14 LBS. EA. <sup>4</sup>	24.5 LBS. EA.	24.5 LBS. EA.	24.5 LBS. EA.	24.5 LBS. EA./ 32.5 LBS. EA.	24.5 LBS. EA./ 38 LBS. EA.	38 LBS. EA.	55 LBS. EA./60 LBS. EACH	63.5 LBS. EA.
BATTERY REQUIREMENTS8	(2)12AH	(2)12AH	(2)12AH OR (2)18AH	18AH	(2) U-1	(2) U-1	(2) U-1	(2) U-1 OR (2) 40AH	(2) U-1 OR (2) NF-22	(2) NF-22	(2) GROUP 27 OR (2) GROUP 24	(2) GROUP 27
PER CHARGE RANGE (MAX.) <sup>2,10</sup>	UP TO 6 MILES	UP TO 8 MILES	3W: UP TO 10 MILES <sup>11</sup> 4W: UP TO 7.5 MILES <sup>11</sup>	UP TO 12 MILES	UP TO 13 MILES	UP TO 13 MILES	UP TO 15.5 MILES	UP TO 17 MILES	3W: UP TO 18 M/NF-22 3W: UP TO 10 M/U-1 4W: UP TO 13 M/NF-22	UP TO 14 MILES	G27: Up to 28.94 miles G24: Up to 21.70 miles	UP TO 20 MILES
BATTERY CHARGER	OFF-BOARD, 2A	OFF-BOARD, 2A	OFF-BOARD, 2A	OFF-BOARD, 2A	OFF-BOARD, 3A	OFF-BOARD, 3A	OFF-BOARD, 3A	OFF-BOARD, 5A	OFF-BOARD, 5A	OFF-BOARD, 5A	OFF-BOARD, 8A	ON-BOARD, 5A
SUSPENSION	N/A	N/A	N/A	N/A	N/A	N/A	N/A	3-W REAR/ 4-W FRONT & REAR	3-W REAR/ 4-W FRONT & REAR	FRONT AND REAR	FRONT AND REAR	REAR
MAXIMUM WEIGHT	275 LBS.	260 LBS.	275 LBS.	300 LBS./325 LBS.	300 LBS.	300 LBS.	400 LBS.	350 LBS.	500 LBS.	400 LBS.	400 LBS.	400 LBS.
CAPACITY STANDARD BODY COLORS	RED, BLUE <sup>7</sup>	RED, BLUE <sup>7</sup>	RED, BLUE, SILVER <sup>1</sup>	RED, BLUE, SILVER <sup>1</sup>	CANDY APPLE RED, VIPER BLUE	CANDY APPLE RED, VIPER BLUE	CANDY APPLE RED, VIPER BLUE	CANDY APPLE RED, VIPER BLUE, CHAMPAGNE	CANDY APPLE RED, VIPER BLUE	CANDY APPLE RED, VIPER BLUE, SILVER	CANDY APPLE RED, VIPER BLUE, SILVER	CANDY APPLE RED, VIPER BLUE
AVAILABLE POWER ELEVATING SEATING	N/A	N/A	N/A	N/A	N/A	STANDARD	N/A	YES (SPECIAL ORDER)	YES (SPECIAL ORDER)	N/A	N/A	YES (SPECIAL ORDER)
WEIGHT OF HEAVIEST PIECE⁵	28 LBS. (3-WHEEL) (FRONT SECTION)	28 LBS. (3-WHEEL) (FRONT SECTION)	28 LBS. (3-WHEEL) (FRONT SECTION)	32.5 LBS. (3-WHEEL) (REAR SECTION)	48.5 LBS. (3-WHEEL) (FRONT SECTION)	59.5 LBS. (3-WHEEL) (FRONT SECTION)	54.5 LBS. (FRONT SECTION)	56 LBS. (3-WHEEL) (FRONT SECTION)	66.5 LBS.(3-WHEEL) (FRONT SECTION)	95 LBS. (FRONT SECTION)	N/A	N/A
ion contained herein is correct at the time of publication; e right to alter specifications without prior notice. Speed & th user weight, terrain type, bottery charge, bottery condition ure. Due to manufacturing tolerances and continual product		33.5 LBS. (4-WHEEL) (FRONT SECTION)	32.5 LBS. (4-WHEEL) (FRONT SECTION)	35 LBS. (4-WHEEL) (FRONT SECTION)	45 LBS. EACH (4-WHEEL) (FRONT/REAR SECTION)		61 LBS. (FRONT SECTION)	65.5 LBS. (4-WHEEL) (FRONT SECTION)	75.5 LBS. (4-WHEEL) (FRONT SECTION)			
length, width, turning radius and ground clearance can be									115 1201 51			5,

The information of we reserve the rigl range vary with us and tire pressure. improvement, length, width, turning radius and ground clearance can be subject to variance of + or -3 %.