INSTALLATION GUIDE

QUESTIONS OR DIFFICULTIES?



Call us at 402-421-3311 or email info@vahallan.com


→ **START HERE:** *DO NOT BEGIN* UNTIL YOU HAVE READ THESE GUIDELINES!

RANDOM PATTERN WALL COVERING


TILED | DO NOT TRIM











WALL PREP

Level 4 finish, clean, and primed with a tinted, pigmented acrylic primer such as Roman PRO-777.

ADHESIVE

Clear, strippable, or heavy-duty wallcovering adhesive such as Roman PRO-880.

PATTERN MATCH: RANDOM

TRIMMING

Die-cut tiles, do not trim.

TOOLS

Wallpaper brush and plastic smoother.

STORAGE

Wallcovering should be installed within 30 days or receiving. Prolonged storage may damage the wallcovering. Please contact us immediately for storage recommendations if you are unable to install within 30 days of receipt.

WALL PREPARATION

Walls should be finished to a Level 4 drywall standard, thoroughly cleaned of dust and debris, and primed with a pigmented acrylic primer—such as Roman PRO-777—designed specifically for wall protection. The primer should be tinted to closely match the color of the wallcovering.

INSPECTION

Carefully inspect all wallcovering prior to installation to verify correct color, pattern, quantity, and condition. Be aware that additional material may not match the original dye lot. Vahallan is not responsible for the cost of replacing wallcovering that was incorrectly inspected or installed.

RETURN POLICY

After hanging the first three drops (or tiles), carefully inspect the installation for any faults or defects. If any issues are found, stop work immediately and notify the manufacturer. In some cases, it may be advisable to remove the installed material before it dries, as removal and replacement become more difficult afterward.

No claims will be accepted after more than three drops have been installed. Vahallan is not responsible for installation costs related to improperly installed material or delayed reporting of defects.

TRAVERSE

PRODUCT SPECIFICATIONS

APPLICATION

TILES

RECTANGLE TILE SIZE

9" x 29", 18"x 29", 14"x 42", 14"x 49", 29" x 58"

SQUARE TILE SIZE

14.5" X 14.5", 29" X 29"

REPEAT AND MATCH

NO REPEAT. RANDOM PATTERN MATCH.

TOOLS | STANDARD

A plastic smoother or wallpaper brush may be used to install this wallcovering. It is also safe to gently wipe the surface with a delicate or microfiber cloth. For trimming, a trim guide or putty knife may be used to protect the surface while cutting.

HANDLING

Please handle carefully. Do not fold or crease the wallcovering. If paste gets on the face of the product, do not scrub, gently wipe or blot with a towel.

BOOKING | SHORT

After pasting, allow wallcovering to set by carefully folding the pasted sides together (do not crease). The wallcovering should remain "booked" for 30-60 seconds. Longer booking may cause the wallcovering to become harder to handle and could cause damage.

PATTERN MATCH | RANDOM

This wallcovering features a random match pattern, allowing strips to be applied in any order or orientation. Reversing is not required but may be done if helpful.

VARIATION

This is a hand painted product and may contain natural variation from piece to piece. This material has been inspected but may still include small imperfections or blemishes. Please carefully inspect and **only hang if you are 100% satisfied with the finish.** Please contact the manufacturer immediately if you believe the material to be defective. Vahallan is not responsible for the cost of replacing wallcovering that was insufficiently inspected.

ADHESIVE

We recommend using a clear, strippable, or heavy duty wallcovering adhesive such as Roman PRO-880 or Roman PRO-838. Paste can be applied to the wallcovering back, wall, or both (Velcro method).



WRAPPING

This wallcovering is suitable for wrapping inside and outside corners.



TRIMMING

This wallcovering has been die-cut and is designed to align in a nearly perfect grid on the wall.

However, slight trimming may be necessary, as tiles can stretch or vary slightly in size due to the handcrafted nature of the product.



SEAMS/PANELING

This die-cut pattern is designed to fit together precisely, though some visible seams may remain, adding to the product's natural beauty and variation.



QUESTIONS OR DIFFICULTIES?

Call us at 402-421-3311 or email info@vahallan.com

Vahallan will not be responsible for any labor claims under any circumstances.