

Invisible Oil Primer



Primer for Invisible Oil

Invisible Oil Primer is a water-based wood primer with excellent adhesion, that gives wood a matt, untreated appearance when combined with WOCA Invisible Oil. Invisible Oil Primer is the first stage in a high quality water-based oiling system and should therefore be used together with WOCA Invisible Oil. The Invisible system has been developed for use with light wood varieties, where a high oiling quality and newly-sanded, untreated appearance are required. The range gives the floor a surface that is both comfortable to walk on and soft to the touch. The floor is also left with a soft, water-resistant surface that is easy to clean and maintain.

- Gives the floor an untreated appearance
- Resistant to liquids such as water, coffee, tea and red wine
- Gives the wood a beautiful, breathable surface
- Indoor climate certified

Application area

For priming untreated, new or newly-sanded wooden surfaces in light wood varieties. Should be treated after priming with Invisible Oil.

Work description

Preparation

It is important that the product, the room and the floor are at a temperature between 15 °C and 30 °C and that air humidity is approx. 50 %. Wood humidity must not exceed 12%. Make sure that the room is well-ventilated for optimal evaporation and drying time. The wood must be newly-sanded, with grit 100-150 for the final sanding. Vacuum thoroughly. Wash the floor with WOCA Intensive Wood Cleaner and leave the floor to dry for at least 8 hours before application of the primer.

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

0

Please note

Invisible Oil must be applied when using Invisible Primer. After 24 hours, we recommend that the primed and oiled surface is treated with Invisible Oil Care to improve the floor's resistance to stains and wear.

Drying time

Drying time: 3-4 hours at 68°F

Recommendation: Do not expose the surface to water for the first 7 days while the oil is hardening.

Fully hard: 7 days at 68°F

Technical data

Density: 1.00-1.10 g/ml.

pH-value: pH 7-8

Shelf life: 2 years

Application Temperature: +59-77°F and approx. 50% air humidity.

Coverage: 85-130 sq.ft./L

Colours: Natural

Cleaning of tools: Use warm water

Storage: +50-77°F. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging: 84.535 FL.OZ.

Viscosity: 25-30 Sec. DIN Cup 4

Dilution: Undiluted

Odour: Faint

Solid content: 10-20%

Maintenance and related products

WOCA Denmark A/S
Tværvvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.