

# Maintenance Oil Diamond Active



## Revitalises oil-treated wood

Use Maintenance Oil Diamond Active for the ultimate care and maintenance of your oiled wood floor. This exclusive, low-odour, extremely tough maintenance oil is made from the absolute highest quality raw materials, to benefit both you and your oiled floor. In addition to being very easy to use and assuring minimal product waste, the maintenance oil refreshes the natural, warm glow of the wood and increases resistance to stains, via a unique hyper cross linking technology. Maintenance Oil Diamond Active is suitable for both manual and machine application to oiled floors.

- Resistant to liquids such as water, coffee, tea and red wine
- Resistant to scratches and marks
- Gives the wood a beautiful, breathable surface
- IBR-certified

## Application area

For oiled surfaces.

## Work description

### Preparation

It is important that the product, the room and the floor are at a temperature between 59-86°F and that air humidity is approx. 50 %. Wood humidity must not exceed 12 %. Make sure that the room is well-ventilated for optimal evaporatio and drying time. The surface must be free of grime, grease and wax. Wash the floor with WOCA Intensive Wood Cleaner and leave the floor to dry for a least 8 hours or until it is completely dry.

### Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

### Treatment

0

### Please note

Do not expose the floor to water or clean it for the first 3 days, while the oil is hardening.

### Number of coats

1

## Drying time

**Light use:** 3-4 hours at 68°F

**Drying time when machine polished:** 3-4 hours at 68°F

**Drying time when hand polished:** 24 hours at 68°F

**Fully hard:** 3 days at 68°F

## Technical data

**Declaration:** Drying oils.

**VOC:** 35 g/l. (max)

**Density:** 0.85-0.90 g/ml.

**Shelf life:** 3 years

**Application Temperature:** +59-86°F and approx. 50% air humidity.

**Coverage:** 430-540 sq.ft./L

**Colours:** Natural, White;White

**Cleaning of tools:** Use WOCA Solvent or turpentine

**Storage:** +50-77°F. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

**Packaging:** 84.535 FL.OZ.

**Viscosity:** 15-20 Sec. DIN Cup 4

**Dilution:** WOCA Solvent (does not normally need to be diluted).

**Solid content:** 70-75%

## Maintenance and related products

### Maintaining and cleaning

For daily cleaning, WOCA Natural Soap is recommended, which effectively washes and cares for the wood. Supplement occasionally with WOCA Oil Refreshing Soap, which also adds a little oil to the wood with each wash.

WOCA Denmark A/S  
Tværvej 6  
DK - 6640 Lunderskov  
+45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*