

Natural Sealer



Water Based Wood Floor Sealer

Natural Sealer is a one component sealer that keeps the natural color of the wood while protecting it from side bonding, tannin penetration. This product is designed to build quickly and give a great foundation for one of WOCA's waterbased finishes to be over it. Natural Sealer is extremely low VOC content make it a great choice for those worried about indoor air quality. It is quick to sand or recoat in just 120 minutes. WOCA's sealers are made with ease of use in mind with technology that significantly reduces overlap marks and increases flow to make the toughest job easy. For complete application, care and use information please see our website or TDS.

- Quick-drying, sandable after 120 minutes
- Reduces side-bonding
- Minimizes penetration of tannic acid
- Gives the wood a light colour

Application area

Only suitable for sealing untreated or sanded wood surfaces. Ideal for all species of wood.

Work description

Preparation

It is important that both wood and product have a temperature of min. 59°F (preferably around 68°F) and air humidity of approximately 40-60 %. Make sure that the room is well-ventilated for optimal evaporation and drying time. Untreated floors must be free of dirt, grease, wax and dust. Floors that have been finished previously must be sanded down to bare wood before the sealer is applied. Vacuum thoroughly and tack the floor afterwards if necessary, using a tightly-wrung water-soaked cloth. Shake the Natural Sealer thoroughly before use.

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

1 x sealer + 2 x WOCA floor finish. Apply Natural Sealer undiluted with brush or roller and allow the surface to dry. Apply a layer of topcoat with one of the WOCA floor water based finish and sand between coats using grit 150-200 sandpaper. Vacuum carefully and apply another 1-2 topcoats.

Please note

Only 2 coats of Natural Sealer and/or floor finish can be applied each day.

Drying time

Drying time: 1-2 hours at 68°F

Recommendation: If drying times are not followed, this can result in poor adhesion and reduced resistance. For each layer of Natural Sealer, drying times will be increased. High temperature and low air humidity will reduce drying times. Low temperature and high air humidity will extend drying times.

Technical data

VOC: 75 g/l. (max)

Density: 1.00-1.10 g/ml.

pH-value: pH 7-8

Shelf life: 2 years

Application Temperature: +59-77°F and approx. 50% air humidity.

Coverage: 325-490 sq.ft./Gal

Colours: Colorless - Satin

Cleaning of tools: Use water

Storage: +50-77°F. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging: 1 Gallon, 169.070 FL.OZ.

Viscosity: 25-30 Sec. DIN Cup 4

Dilution: Undiluted

Odour: Faint

Solid content: 30-40%

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.