

Natural Soap



Cleaning and protection of oiled wood

Clean and maintain oiled, waxed and soaped wood surfaces with Natural Soap. This mild, penetrating soap removes dirt and helps prevent the wood from drying out and cracking. It leaves behind a microscopic, breathable soap layer on the surface that maximizes resistance and makes the surface easier to keep clean. Natural Soap is indoor climate labelled and free of perfume and additives.

- Nourishing effect
- For the basic treatment of softwood
- Ideal for floors, furniture, table tops and panels
- For regularly cleaning
- For the basic treatment of softwood

Application area

For cleaning and maintenance of oiled, waxed and soaped wood surfaces.

Work description

Preparation

Daily cleaning is made with vacuum cleaner or broom. The frequency of floor cleaning depends on the wear on the floor. Very dirty floors may be cleaned with Intensive Wood Cleaner before using Natural Soap.

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

Natural Soap is shaken carefully before use. Make sure the pigments are mixed well. 3 ounces of Natural Soap is mixed into 1 gallon of cold water. Damp mop the surface with a well wrung mop. For best results, use two buckets. One with the soap solution and the second with clean water to rinse the dirty mop. Clean the floor with minimum quantity of water – leave soap water on floor briefly in order to dissolve dirt. Remove dirty soap water with hard-wrung mop or cloth and rinse out in bucket with clean water. Always wipe down the surface with soap water and a hard-wrung mop or cloth in order to re-establish the protective soap film.

Please note

Don't use 100% microfiber. For best results, use two buckets. One with the soap solution and the second with clean water to rinse the dirty mop. See technical data sheet for further information.

Drying time

Technical data

Declaration: 15-30% soap – coconut and soya fats, pigments.

pH-value: pH 9-10

Shelf life: 3 years

Coverage: 3,450-4,300 sq.ft./L

Colours: Natural, White;White

Cleaning of tools: Use water

Storage: +50-77°F. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging: 33.814 FL.OZ., 84.535 FL.OZ., 169.070 FL.OZ.

Dilution: Water

Odour: Faint

Mixing ratio: 4.226 FL.OZ. to 169.070 FL.OZ. water.

Maintenance and related products

Maintaining and cleaning

Areas with heavy wear may be maintained with WOCA Maintenance Oil or WOCA Maintenance Gel after cleaning with Intensive Wood Cleaner.

WOCA Denmark A/S
Tværevej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.