

# Neutral Oil 840004



## Fast-drying industrial oxidizing oil for wooden floors

Neutral Oil Industry is an environmentally friendly product based on vegetable oils, water and drying agents. It is used for new or newly sanded wood and creates a neutral finish that resembles untreated wood. The oil offers a good protection of the surface while maintaining the raw wood look.

- Untreated appearance of the wood (invisible look)
- Roller application
- Easy application on a variety of processes
- Fast drying

### Application area

For surface treatment of wooden floors and parquets in solid wood, hardwood and softwood.

### Work description

#### Preparation

The wood must be clean, dry and free from dust.

#### Intermediate sanding grits

Grit 320-400.

#### Sanding grits

Grit 100-120.

#### Treatment

0

#### Please note

Viscosity correction: Correction can be made with a maximum of 5 % water. An extra coat of Industrial Hardwax oil 1505 can be applied giving extra protection.

### Drying time

**Fully hard:** 7 days at 20°C

### Technical data

VOC: 95 g/l, maximum VOC content (A/i (WB)): 140 g/l.

**Density:** 1.00-1.10 g/ml.

**Shelf life:** 2 years

**Coverage:** 25-40 m<sup>2</sup>/L

**Colours:** Natural

**Storage:** +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

**Packaging:** 20 L

**Viscosity:** 80-85 Sec. DIN Cup 4

## Maintenance and related products

### Maintaining and cleaning

The industrial surface treatment can be maintained with WOCA maintenance products

WOCA Denmark A/S  
Tværvej 6  
DK - 6640 Lunderskov  
+45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*