

Reactive Stain



For pre-colouring of tannin-rich wood

A stain specially formulated to create an aged and rustic look on tannin-rich woods in a fast and simple way. It reacts quickly after the application and provides a vibrant and distinctive color depending on the type of wood used. The color is kept intact for a long time, as the stain is very resistant to light. Modern and unique color solutions can be created by using Reactive Stain in combination with WOCA Color Oils.

- Unique look
- Offers a countless number of exciting color options
- The final colour depends on the tannin content in the wood
- Quick color reaction and high color stability

Application area

For colour treatment of tannin-rich wooden floors, furniture and wall panels.

Work description

Preparation

The wood must be clean, dry and free from dust.

Intermediate sanding grits

Grit 400-500.

Sanding grits

Grit 100-120.

Treatment

0

Please note

Viscosity correction: Not recommended. If the color is too dark, water can be added to achieve the right design.

Drying time

Technical data

VOC: 175 g/l, maximum VOC content (A/i (WB)): 140 g/l.

Density: 1.00-1.10 g/ml.

pH-value: pH 8-9

Shelf life: 2 years

Coverage: 190-326 sq.ft./L

Colours: Smoke light, Smoke dark, Mouse Gray, Dark grey, Ebony, Extra Grey

Storage: +50-77°F. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging: 338.140 FL.OZ.

Viscosity: 10-15 Sec. DIN Cup 4

Maintenance and related products

Maintaining and cleaning

The industrial surface treatment can be maintained with WOCA maintenance products

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.