22Ir CuRx Powder Testing 42gr bullets

| L | | | | | | | |
|------------------------------|---|--------------|---------------|-----------------|---|-------|--|
| | Rifles Used | Twist Rate | Barrel Length | COAL | Notes Custom rifle - Barrel fouled with lead bullets prior to testing | | CUTTING EDGE BULLETS |
| | Custom Build | 1-6" | 21.5" | 1.213" | | | |
| CAUTION: | Ensure Bullet exits the barrel on minimum charge loads before firing another round and proceeding up in charge. Go up in charge very small amounts compared to center fire cartridges. Never start at Maximum charge noted. | | | | | | |
| Note: | | А | | | | | r loading rimfire cartridges. |
| Slowest to Fastest | | | | | | | |
| | | | | Velocity | | | |
| Powder | Max Load(gr) | Min Load(gr) | <u>Rifle</u> | <u>(at max)</u> | Accuracy vel. | Group | Notes |
| Win 296 | | | | | | | |
| H110 | | | | | | | |
| H Lil'Gun | | | | | | | |
| Viht N110 | | | | | | | |
| Alliant Steel | | | | | | | |
| AA#9 | 4.30 | 3.50 | Custom | 1577 | ? | <1/2" | Excellent potential. Shot 1/2" group during ladder test with 1 shot per charge. 9 different charges. Gen 1 |
| Enforcer | 4.50 | 5.50 | Custom | 1577 | 1 | <1/2 | with 1 shot per charge. 9 different charges. Gen 1 |
| Alliant 2400 | 3.40* | 3.00 | Custom | 1223 | ? | ? | Possible good subsonic powder. Test further. |
| Alliant 410 | 3.40 | 3.00 | Custom | 1223 | | • | rossible good subsonic powder. rest further. |
| Longshot | 2.70 | 2.10 | Custom | 1505 | 1400-1500 | 3/8" | Powder shows excellent accuracy with multiple charges. 3/8" consistently |
| | | | | | | | Showed good potential. <1/2" group in 2 loads tested. 19fps ES. Test further. Case blew at 3.64gr(lower than |
| AA#7 | 3.60 | 2.60 | Custom | 1640fps | ? | <1/2" | AA9) Gen 1 |
| Blue Dot | | | | | | | |
| Viht N350 | 2.52 | 2.10 | Custom | 1405(11ES) | same | <1/4" | Excellent accuracy and velocity spread. Produced 1/4" group during ladder from 2.49-2.52gr 4 shots total. Also 1/4" group at max charge. |
| Viht 3N37 | 2.84 | 2.40 | Custom | 1446(13ES) | 1400-max | 3/8" | Excellent accuracy with velocity ES of 15fps and less. Test further |
| Ramshot Silhouette | | | | | | | |
| Ramshot Silhouette | | | | | | | |
| AutoComp | | | | | | | |
| HS-6 | 3.24 | 2.50 | Custom | 1549 | 1535 | <.5" | Excellent Accuracy with bad mirage. Test further to reduce velocity ES |
| AA#5 | 2.96 | 2.50 | Custom | 1391 | 1300-1400 | .3" | Excellent accuracy. Test further to reduce velocity ES |
| IMR HySkor 800X | | | | | | | |
| IMR HySkor 800X Viht N340 | 2.38 | 2.00 | Custom | 1394 | 1335(20ES) | 1/2" | Showed excellent accuracy during ladder test. 1/2" group was horizontal. |
| Win. WSF | | | | | (2020) | _, _ | |
| Herco | | | | | | | |
| Power Pistol | | | | | | | |
| Universal | | | | | | | |
| Unique | 3.40 | 1.90 | Custom | 1390 | 2.3gr-1330 | 3/8" | Maximum case fill. |
| Alliant 20/28 | | | | | | | |
| Ramshot Zip | | | | | | | |
| Winchester WST | | | | | | | |
| Titegroup | | | | | | | |
| Viht N110 | Too slow | | | | | | |
| Alliant Steel | Too bulky | | | | | | |