



# Eazy<sup>V3</sup> Electronic Coffee Tamper - Product Specifications

| Specification                          | Details  | Other information  |
|--|--|--|
| <b>Guarantee</b>                       | Lifetime   | -  |
| <b>Net weight</b>                      | 7.5kg  | -  |
| <b>Materials</b>                       | Stainless steel and/or powder-coated metal   | -  |
| <b>Footprint (D x W x H)</b>           | 230 x 145 x 300mm  | Top of machine acts as additional storage space for other equipment e.g. EFTPOS printer, mobile phone.   |
| <b>Input</b>                           | <ul style="list-style-type: none"> <li>Voltage: 220 – 240Vac</li> <li>Frequency: 50Hz</li> <li>Fuse rating: 5A</li> </ul>  | -  |
| <b>Motor specifications</b>            | <ul style="list-style-type: none"> <li>Input Voltage: 12V DC</li> <li>Stroke: 50mm</li> <li>Max Load: 400N,</li> <li>Speed: 25mm/sec</li> </ul>  | <ul style="list-style-type: none"> <li>Average filter basket, 8mm plus 7.5mm into coffee grind = tamping speed of less than 1 second.</li> <li>Motor comes with cast iron gears.</li> <li>Compressed &gt;400k presses as at year commencing 2021.</li> </ul> |
| <b>Power</b>                           | 50W  | -  |
| <b>Plug type</b>                       | All  | -  |
| <b>Compression settings</b>            | One or two per cycle   | -  |
| <b>Tamper diameter</b>                 | 58.4mm   | -  |
| <b>Suitable for</b>                    | Every coffee machine   | -  |
| <b>Portafilter compatibility</b>       | Naked, single & double   | -  |
| <b>Naked portafilter compatibility</b> | Yes  | -  |
| <b>Non-stick tamper head finish</b>    | Yes  | -  |
| <b>Cleaning mode</b>                   | Yes  | Pin-code operated (no Alan key required).  |
| <b>Tamping depth</b>                   | Up to 50mm   | -  |
| <b>Force adjustment</b>                | 10-30kg in one kg increments. Can be calibrated to compress greater weight by special request.   | Force compression accurate and individually calibrated & tested against load-cell in factory before dispatch for each motor capability   |
| <b>Other features</b>                  | <ul style="list-style-type: none"> <li>Electronic touch screen display showing tamping pressure, temperature &amp; humidity reader and date &amp; time.</li> <li>Daily, monthly &amp; yearly tamping press counter.</li> <li>Four themed display options.</li> <li>Safety features (PIN Code protected).</li> <li>Electronic user guide (on-screen).</li> </ul>  | -  |
| <b>Comes with</b>                      | <ul style="list-style-type: none"> <li>Coffee Grind Tray (captures left over coffee grind).</li> <li>Comes with a soft-top patch for top of unit.</li> <li>Entry bumper.</li> <li>Coffee cleaning brush.</li> </ul>  | -  |
| <b>Available colours</b>               | <ul style="list-style-type: none"> <li>Stainless steel</li> <li><a href="#">Black</a></li> <li><a href="#">White</a></li> <li><a href="#">Steel Pearl (Charcoal)</a></li> </ul>  | Other colours available on special request   |
| <b>Certifications</b>                  | <ul style="list-style-type: none"> <li>IEC 60335-2-14 Edition 5.2</li> <li>IEC 60335-1 Edition 5.2</li> <li>EN 60335-2-14:2006 + A1:2008 + A11:2012/AC:2013</li> <li>EN 60335-1:2012/AC:2014 + A11:2014</li> <li>EN 62333:2008</li> <li>AS/NZS 60335.2.14:2013</li> <li>AS/NZS 60335.1:2011 + A1-A3</li> <li>AS/NZS CISPR 14.1:2013 (CISPR 14-1: 2011 Ed 5.2)</li> <li>CFR FCC Part 15</li> <li>Subpart B</li> <li>ANSI C63.4: 2014</li> </ul> | -  |