

STILL THE ONLY CUBE OF ITS KIND.



Plumbing:

3/4" FPT potable water inlet 3/4" FPT bin drain 3/4" I.D. flex tubing cuber drain 3/8" FPT condenser (liquid-cooled) inlet 1/2" FPT condenser (liquid-cooled) outlet

Exterior Finish: 300 Series stainless steel

Refrigeration System: Thermostatic expansion valve controlled R-404A-HFC

Clearance Requirements: Allow 4" left side, 8" right side and back, and 6" top for ventilation and utility connections.

Condenser Heat Rejection: BTUH/kW/Ton 6,500/1.91/0.54 avg. 8,750/2.6/0.729 peak



X-SERIES

GBX560 - ICE MACHINE

THE X-SERIES SIGNATURE

Produces up to 500lbs of ice per day! The X-Series from Kold-Draft features rounded corners, plastic top panels, plastic louvers and an LCD display. X-Series machines are stackable with other X-Series machines. Double the capacity in the same footprint!

Dimensions/Weight							
Description	Dii	Ship Weight					
Description	W	D	Н	Ship Weight			
Air Cooled	42.3" (107.4cm)	31.1" (79cm)	17" (43.2cm)	215lb (97.5kg)			
Liquid Cooled	42.3" (107.4cm)	25.63" (65.1cm)	17" (43.2cm)	200lb (90.7kg)			

Recommended Operating Requirements: MAX. MIN. Room Temp. 45°F (7°C) 110°F (43°C) Water Temp. 45°F (7°C) 90°F (32°C) Voltage 208-230 198V 253V Voltage 115 104V 126V

Potable Water Pressure 20 PSIG (137 kPa) 100 PSIG (689 kPa) Liquid-Cooled Condenser Pressure 100 PSIG (689 kPa) 20 PSIG (137 kPa)

GBX5	GBX560 Series Daily Capacities: Lbs. of ice per 24 hours per unit										
Model	Electrical	Condenser	Cube	Ice Ca 24 Hours		Energy Input 90°F (32°C) 70°F (21°C)		gal/100# (l/kg) [) / 70°F (21°C)	— мса	МОР	Required Condenser
Number	Volt/Hz/Ph	Condenser	Size	70°F (21°C) 50°F (10°C) Ambient/Water	90°F (32°C) 70°F (21°C) Ambient/Water	kWh/100 lbs. (kJ/kg)	Potable	Condenser			
GBX561AC	115/60/1	Air Cooled	Full Cube	490 (222)	402 (182)	5.9 (468)	14.0 (1.2)	n/a	14	30	n/a
GBX564AC	208-230/60/1	Air Cooled	Full Cube	483 (219)	413 (187)	6.0 (476)	13.9 (1.2)	n/a	7	20	n/a
GBX561LC	115/60/1	Liquid Cooled	Full Cube	559 (224)	474 (215)	4.8 (381)	14.7 (1.2)	157 (13.1)	13	30	n/a
GBX564LC	208-230/60/1	Liquid Cooled	Full Cube	543 (246)	456 (207)	4.9 (389)	14.0 (1.2)	162 (13.5)	7	20	n/a

Compatible					
Model	Width	Depth	Height (w/ 6" legs)	Capability (lb)	Weight (lb)
KDB650	42"	35″	41"	650	182

Accessories		
Model Number	Description	Shipping Weight (lb)
102149501	GBX560/GBX1060 Series on top of GBX560/GBX1060 Series Stacking kit	5
DR3-GB	GB/GBX Series Drain Riser Kit, 3"	20

KOLD-DRAFT recommends all ice machines have water filtration. Please reference water filtration specification sheet.









KOLD-DRAFT • 101 Corporate Woods Parkway, Vernon Hills, IL 60061 (800) 840-9577 • info@kold-draft.com • www.kold-draft.com

an Ali Group Company

