



- Pure solid softdrawn American-mined copper
- Every roll tested for voltage leakage and continuity
- Solid wood spools
- **UL listed and CSA approved**

UL-300V MULTI-CONDUCTOR IRRIGATION CABLE



(Price sheet available upon request)

- 300 Volt direct burial irrigation cable
- Nylon rip cord
- Available in 18 AWG
- 2-13 conductors available
- 14-1 AWG solid bare copper with PVC insulation for UL-600V
- Ultra-flexible for fast installations
- Available in 8, 10, 12, 14, 16 and 18 AWG with 2 conductors

UL-600V - UF SINGLE-CONDUCTOR WIRE



LOW VOLTAGE LIGHTING CABLE



CORD SETS:

- 16/3 3' Right Angle Plug 100 per case
- 16/3 3' Straight Plug 100 per case
- 16/3 6' Right Angle Plug 50 per case
- 16/3 6' Straight Plug 50 per case

Lamp Cord: 250' spools, 500' per box

18-2

16-2

UF UL AWG: weight per 1000' UF UL AWG weight per 1000

12-1-2500' spool	37	10-1-2500'	52
14-1-2500' spool	28	16-1-2500'	17

UL LISTED LOW VOLTAGE LIGHTING WIRE ON WOOD SPOOLS:

8-2 250' SPOOL	10-2 500' SPOOL	12-2 500' SPOOL
16-2 500' SPOOL	18-2 500' SPOOL	

CONDUCTOR WIRE / PUMP CABLE



18AWG UL LISTED MULTI CONDUCTOR WIRE

# conductors	weight per 1000'	# conductors	weight 1000'
2	26	7	60
3	30	8	68
4	40	9	72
5	48	10	86
6	54	13	105

PUMP CABLE

	<u>weight</u>
Twisted w/ ground	
14-2 solid	65
14-3 solid	86
12-2 solid	91
12-3 solid	122
10-2 solid	132
10-3 solid	176
8-2 stranded	195
8-3 stranded	270
6-3 stranded	402
4-3 stranded	564
Flat w/ground	
14-2 stranded	69
14-3 stranded	91
12-2 stranded	95
12-3 stranded	125
10-2 stranded	136
10-3 stranded	182
8-2 stranded	217
8-3 stranded	247
4-3 stranded	562
Heavy duty flat jacketed w/ground (stranded)	
14-3 stranded	152
12-2 stranded	151
12-3 stranded	200
10-2 stranded	203
10-3 stranded	269
8-2 stranded	262
8-3 stranded	384
6-3 stranded	532
4-3 stranded	733
2-3 stranded	1048