




Overall Thickness: 7.5mm (includes 1mm cork)
Installation Method: Float
Warranty: Limited Commercial | Limited Light Commercial | Limited Residential

7" x 48.6" | 16.57 sf/ctn



ALTON
NCQ-2764




CALIENTE
NCQ-2634



FAIRHOPE
NCQ-2950



HOOD RIVER
NCQ-2627



WHITEVILLE
NCQ-2298

Wear Layer:
Slip resistant, anti-microbial ceramic bead enhanced UV finish
.55 mm (22 mil) wear layer


Core:
Waterproof thermoplastic composite
Thickness - 3.9 mm

Backing:
Type - Natural Cork
Thickness - 1 mm

Painted Bevel

Tight Lock
Locking System

IIC = 71 according to the standard ASTM E492-09



- FINISH**
Anti-bacterial
- HIGH-DEFINITION DEEP STRUCTURED DECORATIVE LAYER**
providing realistic hardwood/tile look & feel
- PREMIUM HIGH-DENSITY VINYL**
for additional comfort, soft underfoot and sound absorption
- SOUND ABSORBENT LAYER**
allowing for improved sound absorption
- RIGID LIMESTONE-BASED COMPOSITE CORE**
100% Waterproof
Rigid and stable
Indentation resistant
- HYPOALLERGENIC CORK BACKING**
naturally hypoallergenic & waterproof cork is THE natural solution for extra protection, sound absorption & an extra soft underfoot

