Prestige



RECIPROCAL


















RECIPROCAL

Style: 7F0P6 Reciprocal

Construction: Multi-Level Pattern Loop

Fiber: 100% Pivotal™ PET

Dye Method: Solution Dyed

Tufted Weight: 15 oz/yd² Gauge: 1/10

Gauge: 1/10 Stitches per Inch: 9

Finished Pile Thickness:

O.118"

Total Thickness:

0.24"

Average Density: 4576 oz/yd³
Product Size: 24" x 24"

Primary Backing: Synthetic

Primary Backing: Synthetic Secondary Backing: Stratworx

Protective Treatments: Inherent Stain Resistance

TESTING

Radiant Panel: Class I (ASTM E-648)
Smoke Density: <450 (ASTM E-662)
Static Control: <3.5 kv (AATCC-134)
Antimicrobial: Passes (AATCC-174)*

*when using 5036S adhesive

RECOMMENDED ADHESIVES

ADA Compliant:

This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

PACKAGING

Tiles per Carton: 20 pcs
Yards per Carton: 8.88 sq yd

INSTALLATION METHODS

$\uparrow \rightarrow$	S5000	5036S Antimicrobial (AATCC-174)
↑ → → ↑	5100S	S5001 [1 gal pail]

1/4 Turn

WARRANTIES

10 Year Commercial Limited Warranty with Stain & Color for Strataworx®

ENVIRONMENTAL CERTIFICATION

Green Label Plus Certification Number GLP8233

Specifications are subject to nominal manufacturing variance.

Material supply and/or manufacturing processes may necessitate changes without notice.