





Versatile:

It can be easily cut to size and arranged to fit any space and storage needs. It can be installed in one section or complete wall and even around corners. With the use of our trims, you can have consistent or seamless looks.

It's compatible with accessories from any standard slatwall hanging system with 3" slats. It allows a flexible layout that easily adapts to changing storage needs over time. Accessories can be reconfigured at will.



Easy to install:

Our PVC Slatwall can be easily cut to size with a power tool. To install it, just screw it directly to wood studs, through drywall to wood studs or into concrete and brick.

Each piece has a tongue and grove. Start form the bottom and interlock one with another. Finish your installation with our trims to have the desired look.

Download our complete installation guide for reference.



Easy to Clean:

Just wipe down. Use a damp cloth and clean dirt, marks, or stains.



Long-lasting:

The PVC formulation of our PVC Slatwall is rich in additives.

It won't crack. Color won't fade or wear off over time. Scratches will be less noticeable since the color throughout the thickness of the product.



Water and moisture resistant:

By its nature, PVC is water resistant. Our PVC Slatwall can be hosed down with a water hose. It can be installed in humid environments, and even in marine environments.

Unlike pressboard slatwalls, ours won't absorb moisture, rot, rust and disintegrate or fall apart. It won't support the growth of mold, mildew, or bacteria and it won't be affected by insects or plagues either.



Fire resistant:

PVC is an inherently flame retardant material. It won't light up with fire.



Non Toxic:

Lead free, Phtalates and plasticizer free, formaldehyde free and BPA free



Environment-friendly:


Our PVC Slatwall is made with up to 30% of recycled materials and is 100% recyclable.



PVC SLATWALL



DIMENSIONS



Characteristic	Testing Method	Result	Unit
Density	ASTM-D-792-2013	876.2	kg / m3
Specific Gravity	ASTM-D-792-2013	0.878	-
Impact Resistent Izod	ASTM-D-256-18	.6	lbf-ft / in
Flexural Strenght	ASTM-D-790-17	4,960	lbf / in2
Flex Modulus	ASTM-D-790-17	255,200	Mpa (lbf / in2)
Thermic Expansion	ASTM-E-831-14	80.74	um / (m°C)
Water Absortion	ASTM-D-570-98/2018	0.6	% Incr. Weight 24 h
Water Absortion	ASTM-D-570-98/2018	1.5	% Incr. Weight 72 h
Water Absortion	ASTM-D-570-98/2018	2.4	% Incr. Weight 120 h
Lead Content	AA/ICP	Not Detected	
Phtalates and Plasticizers Content	GC/MS	Not Detected	
Formaldehyde Content	GC/MS	Not Detected	
Bisphenol Content (BPA)	GC/MS	Not Detected	

PRODUCT COMPOSITION TABLE

Footage per Box	Slatwall Size	Pieces per Box	Box size	Box Weight
32 sq. ft	(12 ¼" x 11/16" x 8′)	4	13" x 3.15" X 97.63"	37.47 lb
16 sq. ft	(12 ¼" x 11/16" x 4′)	4	13" x 3.15" X 48.82"	18.74 lb

	%
PVC	52%
Recycled PVC	30%
Calcium Carbonate	5%
PVC Additives	13%
Plasticizer	0%

CONTACTExport Sales

MEX: **+52 55 2122 3990** ext. **229**

MEX: **+52 55 4810 1714**

USA: +1 (424) 296 8697

GROVEPRO
The Groove for organized ideas





