

HydraBarrier® Instructions

Instructions

- 1. Remove HydraBarrier from its packaging.
- 2. Remove filler cap:
 - a. For HydraBarriers with clear cap, using the two plastic loops attached to the fill cap, pull filler cap from HydraBarrier body until it pops out, providing easy access to the spout for filling. Remove outer cap by unscrewing. An inner cap can be removed screwdriver or similar tool.
 - b. For HydraBarriers with Black cap, simply unscrew and remove
- 3. Place HydraBarrier in in front of the area you would like to protect but make sure it is not on any sharp or pointy objects.
- 4. Fill the HydraBarrier using standard garden hose. Continue adding water until the HydraBarrier is at least 90% full. This allows for the maximum surface area of the HydraBarrier water tube to be in contact with the ground resulting in maximum stability when multiple HydraBarriers are in use.
- 5. Once sufficiently filled, replace fill cap back onto the HydraBarrier.



Watershed Innovations, LLC 1 (888) 876-4068

Trademarks and/or registered trademarks of Watershed Innovations, LLC. Information is subject to change without notice. Copyright Watershed Innovations. All rights reserved. HydraBarrier $^{\mathsf{M}}$ and its accessory products are covered by a Limited Liability Warranty good for one month (30 days) from the date of purchase. Please see www.hydrabarrier.com for complete warranty information.