



HydraBarrier

HydraBarrier® Instructions

Instructions

1. Remove HydraBarrier from its packaging.
2. Remove filler cap:
 - a. For HydraBarriers with a clear cap, using the two plastic loops attached to the fill cap, pull the filler cap from the HydraBarrier body until it pops out, providing easy access to the spout for filling. Remove the outer cap by unscrewing. The inner cap can be removed with your fingernail, a small screwdriver, or a similar tool.
 - b. For HydraBarriers with a black cap, simply unscrew and remove the cap.
3. Place the HydraBarrier in front of the area you would like to protect, be sure not to lay it on sharp or pointy objects.
4. Fill the HydraBarrier using a standard garden hose. Continue adding water until the HydraBarrier is at least 85% full. This allows for the maximum surface area of the HydraBarrier water tube to be in contact with the ground, resulting in maximum stability when multiple HydraBarriers are in use.
5. Once sufficiently filled, replace the cap on the HydraBarrier.

Watershed Innovations Company, LLC
(888) 876-4068



Trademarks and/or registered trademarks of Watershed Innovations Company, LLC Information is subject to change without notice. Copyright Watershed Innovations Company, LLC. All rights reserved. HydraBarrier™ and its accessory products are covered by a Limited Liability Warranty good for one month (30 days) from the date of purchase. Please see www.hydrabarrier.com for complete warranty information.