

APP KHL-20 Submersible Water Pump

The APP KHL-20 pump has a rugged cast iron pump body and vortex impeller, combined with a corrosion resistant 304 stainless steel motor casing.

It has a stainless-steel shaft that is fitted with a double mechanical (pump side: silicon carbide, motor side: carbon ceramic).

The powerful motor has an internal starting capacitor and a motor protector. Suitable for the pumping of clean and dirty water, it is suitable for a variety of industrial applications. It has a high head of 25m, with a 50mm outlet.

The pump is available as a manual or automatic 230V pump, or a manual 400V 3-phase model.

It is ideal for processing, dewatering, irrigation, water features and fixed installations.

Maximum depth of immersion is 6 metres. Supplied with 10 metres of heavy duty rubber power cable. Supplied complete with a 2-year warranty.



Model	KHL-20	KHL-20A	KHL-20A 400V
Manual/ Auto	М	А	М
Outlet/ mm	50	50	50
kW	1.50	1.50	1.50
Volt	230	230	400
Flow Ltr/ min	400	400	400
Head/ m	25	25	25
Free Passage/ mm	12	12	12
W x L x H/ mm	208 x 375 x 590	208 x 375 x 590	208 x 375 x 590
Weight/ Kg	36	36	36

Suitable for:

- Dewatering
- Water features
- Irrigation
- Fixed installations
- Processing

