



FPS PUMPS

Mizar and Mizar VOX Submersible Pump

This series of pumps from Mizar in stainless steel are resistant to corrosion. This makes the Mizar pumps perfect for processing, industry and final effluent. The Mizar pumps can be utilised with both clean and dirty waters.



Suspended solids which are up to 10mm in diameter can be pumped with The Mizar 30 and Mizar 60, while the Mizar Vox can pump solids of up to 20mm.

Ideal if space is limited or restricted, the Mizar pumps can also be used when only partially submerged. It has a top outlet design, which allows the cooling of the motor. The liquid temperature is recommended to go no higher than the maximum of 35°C when fully submerged and 25°C when partially submerged.

In both light industrial and domestic applications, it performs exceptionally well and is highly-reliable. The Mizar pumps are designed to ensure they deliver outstanding service in challenging situations.

There is a special D-shaped handle which allows the Mizar pumps to be transported with ease, or to have a rope attached to them.

The Mizar pumps are not recommended for use in ponds and they come with 10m of heavy duty rubber power cable supplied as standard.



- Suitable for:**
- Dirty water
 - Pumping solids up to 20mm
 - Submerged use

Model	Mizar 30	Mizar 30	Mizar 30	Mizar 30	Mizar 60	Mizar 60	Mizar 60	Mizar 60	Mizar VOX	Mizar VOX	Mizar VOX	Mizar VOX
Manual/ Auto	M	A	M	A	M	A	M	A	M	A	M	A
Outlet /mm	32	32	32	32	32	32	32	32	32	32	32	32
Kw	0.25	0.25	0.25	0.25	0.45	0.45	0.45	0.45	0.45	0.45	0.45	0.45
Volt	110	110	230	230	110	110	230	230	110	110	230	230
Flow Ltr/min	150	150	150	150	225	225	225	225	175	175	175	175
Head /m	7	7	7	7	10	10	10	10	7	7	7	7
Free Passage /mm	10	10	10	10	10	10	10	10	20	20	20	20
W x L x H /mm	0154x23 4	0154x23 4	0154x23 4	0154x23 4	0154x23 4	0154x23 4	0154x23 4	0154x23 4	0154x26 4	0154x26 4	0154x26 4	0154x26 4
Weight /Kg	4.9	5.2	4.9	5.2	5.6	5.8	5.6	5.8	5.9	6.1	5.9	6.1