accuc@ld

VT65MLVAC456ADA



32.38" x 23.63" x 23.5" (H x W x D)

Built-in undercounter ADA height -30°C all-freezer certified to NSF/ANSI 456 for vaccine storage, with NIST calibrated thermometer/alarm

Highlights:

Certified to NSF 456 for the storage of vaccines

Low temperature operation ideal for preserving certain pharmaceuticals

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Product Features:

Certified to NSF/ANSI 456 Vaccine Standard Designed and tested to comply with the new NSF vaccine storage standards through an independent laboratory	
Reliable temperature stability	Engineered to store vaccines and other select pharmaceuticals under stable temperature conditions
Slim undercounter dimensions	24" footprint is ideal for use under the counter
ADA Compliant height	Sized at 32" high (32.38" to hinge cap) to fit under lower counters complying with ADA guidelines
Built-in capable	Front-breathing design allows built-in installation under counters
Low temperature operation	Preset and locked at -30°C to prevent accidental adjustments. Range can be adjusted between -15° and -35°C by contacting our technical support team
Microprocessor control panel	Electronic controls for more precise temperature management, with temperature readout and controls externally located for added convenience
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range
NIST calibrated temperature display	Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button

accuc@ld

VT65MLVAC456ADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.38" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.5" (65 cm)
Depth with door at 90°	46.0" (117 cm)
Capacity	1.85 cu.ft. (52 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S to NSF 456
Amps	1.3
Weight	105.0 lbs. (48 kg)
Shipping Weight	110.0 lbs. (50 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101086903
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	24.25" (62 cm)
Interior Width	17.63" (45 cm)
Interior Depth	
Interior Depth	17.0" (43 cm)
Thermostat Type	17.0" (43 cm) Digital
·	
Thermostat Type	Digital
Thermostat Type Fan Type	Digital Exterior
Thermostat Type Fan Type Refrigerant Type	Digital Exterior R134a
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount	Digital Exterior R134a 2.8 oz.
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI	Digital Exterior R134a 2.8 oz. 235.0
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI	Digital Exterior R134a 2.8 oz. 235.0 70.0
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs	Digital Exterior R134a 2.8 oz. 235.0 70.0
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Interior Drawers	Digital Exterior R134a 2.8 oz. 235.0 70.0 4 Yes
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Interior Drawers Drawers Qty	Digital Exterior R134a 2.8 oz. 235.0 70.0 4 Yes

Temperature Range



