



IP Phone

Model: C66

Gigabit



[www.cortelco.com](http://www.cortelco.com)

1703 Sawyer Road, Corinth, MS 38834

(800)288-3132

and correlative RFCs.  
 nnect to 6 SIP servers at the same time.

igh/low, G.729 a/b, G.722, G.723.1, G.726-32, iLBC, AMR, AMR-WB Codexs may be  
 cancellation  
 th 96 ms max filter length in speakerphone mode  
 3, AGC, Jitter Buffer

ic, MD5)  
 illing  
 833, DTMF Relay  
 s 3 User-Defined Musical Ring Tones

64)

for other features

book, History, Redial) - Programmable for other features

an, Anonymous Call Reject, DND, Caller ID  
 d, Transfer (Blind/Attended), Hold, Conference, Redial, Click to Dial  
 g, Missed Calls - 300 records each  
 acklist 100 Records  
 ion Modules  
 r Call

t Ports (WAN/LAN)  
 ode

erver  
 wall, Open VPN

- QoS with DiffServ
  - Ping, Trace Route, Telnet Client
- Maintenance and Management**
- Management via web, telnet or keypad
  - User and Admin Accounts
  - Firmware Upgrade via HTTPS, HTTP, FTP or TFTP
  - Safe Mode
  - Dual Image Backup
  - Watchdog Timer
  - Syslog
  - Web Capture
  - Autoprovision - Allows upgrade of firmware or configuration  
 DHCP Option 66 or Custom Option  
 Phone Flash  
 TR-069

## Specifications

Power Adapter Input	100 - 240 V
Power Adapter Output	5V @ 1A
WAN Port	RJ-45 10/100/1000 Base-T
LAN Port	RJ-45 10/100/1000 Base-T
Headset Port	RJ-9
EXT	RJ-45
Power Consumption Idle	2.5 W
Power Consumption Active	2.8 W
LCD Size	128 X 64
Operating Temperature	0 - 40° C
Chipset	Broadcom
SDRAM	64 MB
Flash	128 MB
Weight	0.99 kg

