

Mid Office / Contact Centre Headset



Order Code
JPL-400-PM

Order Code
JPL-400-PB

TECHNICAL DATA

| | |
|--------------------|-----------------------------|
| Microphone: | |
| Impedance: | 2.2kΩ |
| Sensitivity: | -32dB ± 3dB at 1kHz |
| Directivity: | Bi-directional |
| Frequency Range: | 50Hz~20kHz ± 6dB |
| Distortion: | Less than 3% |
| Power Supply: | 3V DC |
| S/N Ratio: | More than 58dB |
| Speaker: | |
| Impedance: | 150Ω ± 15% at 1kHz |
| Sensitivity: | 93 ± 3dB at 1kHz 60mV Input |
| Max Input Power: | 100mV |
| Frequency Range: | 100Hz~6800Hz |
| Distortion: | Less 3% at 1kHz 60mV |



PLX OR GN COMPATIBLE QD



FOAM CUSHION & CLOTHING CLIP



HEADSET BAG & HANGING HOOK



JPL-400

Entry level contact centre QD headset suitable for regular phone users.

Overview

| | |
|-----------------|---|
| Features | Single or dual ear Left / right ear side compatible Surround Shield™ noise cancelling microphone Wideband enabled speakers 'Put and stay' ratchet microphone boom arm Overhead, sure-fit fully adjustable headband Fitted with 55mm leatherette ear cushions for maximum all day comfort, 55mm foam ear cushion supplied as spare |
| What's included | Draw string headset storage bag, spare 55mm foam ear cushions, headset hanging hook, clothing clip and Quick Start Guide |
| Headset Weight | Mid-weight Headset, ~ 54g / ~78g |
| Connection | PLX fitted as standard or GN** compatible QD options |
| Compatibility | For full range of bottom leads* and compatibility information - Go to Jpltele.com |
| Certifications | UKCA, CE, FCC, EAC, RoHS, REACH |
| Warranty | 2 Years repair or replacement warranty |
| MOQ | Master Shipping Carton: 40 |
| EAN: | JPL-400-PM: 5060126955955, JPL-400-PB: 5060126955979 |
| SKU: | JPL-400-PM: 575-256-001, JPL-400-PB: 575-256-002 |

PLX = Plantronics compatible QD

* optional to purchase separately.
** GN QD available on special request

