## www.jpltele.com





## **Technical Data**

Microphone:		
Directional:	Uni-directional	
Impedance:	Max. 2.2KΩ	
Sensitivity:	-46±2dB	
Frequency Range:	-52 ~ 20k Hz	
Storage Temp:	-35°C ~ +65°C	
Speaker:		
Impedance:	32Ω ±15% at 0.1V 1000Hz	
Sound pressure:	126dB ± 3dB at 1000HZ	
Frequency range:	FO ~20KHZ(±10dB)	
Operating Temp:	-25°C ~ 50°C	
Storage Temp:	-25°C ~ 60°C	



## JPL-Icon 120-UB4 Designed for users with more than one brand of meeting invite

Connect anywhere, work everywhere, with our plug & play design you can start working immediately with all major video conferencing platforms including: Microsoft Teams, Zoom, Google Meet, 8x8, RingCentral, GoTo, and many more.

## Overview

Features	Dual speaker headset with padded headband	
	Stereo audio, giving clear, crisp sound	
	Fitted with over-the-ear quality soft 75mm leatherette ear cushions	
	Surround Shield™ noise cancelling microphone	
	Plug & play - compatible with any softphone	
	In-line control with volume & mute	Ideal for secure locations or
	Left / right side microphone placement	large roll outs as there is no need, now or in the future,
	 Sound Shield™ Acoustic Shock Protection	to download software
	<sup>'</sup> Put and stay' ratchet microphone boom arm	
	Overhead, sure-fit fully adjustable headband	
What's included	Binaural headset, felt carry pouch, Quick Start Guide	
Headset Weight	148g	
Country of Origin	China	
Compatibility	Over-moulded USB-A & USB-C connectivity	
Certifications	UKCA, CE, RoHS, REACH	
Warranty	2 Years repair or replacement warranty	
MOQ	Master Shipping Carton: 40	
EAN:	5060969682438	
SKU:	575-447-006	



JPL Telecom Ltd, Units 1 & 2, Church Close Business Park, Todber, Sturminster Newton, Dorset DT10 1JH • Tel: +44 (0)1258 820100 • www.jpttele.com