



Specifications For: Starkey SM 5310 1 EAR Ultimate USB Headset with Push to Talk *Non-Noise Cancelling Microphone*. S M5310-MOTH-PTT NNC.

Headset:

- 1 EAR Durable Headband style.
- **This is a non-noise canceling mic**
- Acoustic shock protection receiver
- Microphone static shock protection
- Wideband frequency response, 20Hz to 7.5KHz
- Simple plug into USB port

USB Adapter cord:

- USB 2.0 compliance
- Digital Signal Process (DSP)
- Wideband Frequency response 20Hz – 20KHz
- USB plug and play
- **In-line control board equipped PTT switch**

General Specifications	
Wearing Style	Over-the-Head
Cord Length	2 meters including the bottom cord.
Connector type	USB A-type connector
Quick Disconnect type	No QD (Direct Connection)
Weight	65g
Compatibility	Work with all kinds of soft phones, MS Lync, Skype, all Window versions and all of voice-driven applications
Microphone	Dynamic (This is a non-noise canceling mic)
Mic boom Arm type	Flexible PE bar
Earpiece	XL Oversized Leatherette cushions
Receiver	Wideband Frequency Response with Acoustic shock protection, Mono (Monaural) and Stereo (Binaural) sound
Color	Charcoal Grey
Packing Method	1) Bulk packing <ul style="list-style-type: none"> - Individual PE Zipper bag - 100 bags in outer Carton box 2) Individual Gift Box

	<ul style="list-style-type: none"> - PE zipper bag in individual gift box - 40 boxes in outer Carton box
Warranty	1 year
Compliance	RoHS
Approval	CE, FCC
Optional materials	Headset Hanger, Headset pouch, Leatherette or Foam cushion

Microphone	
Type	Electret condenser
Sensitivity	-44 +/- 3dB @ 1kHz, Vcc=2.0 VDC, RL=2.2K Ohms
Impedance	2.2K Ohms @ 1kHz
Frequency Response	100 ~ 10kHz
Max Input Sound Pressure Level	100dB SPL @1kHz
Harmonic Distortion	0.4% Max
Normal Current Consumption	400 μ A Max, Vcc=2.0 VDC
Operation Voltage	1.6 ~ 5.5 VDC
Receiver	
Size	36mm
Impedance	150 Ohms +/-15%
Frequency Response	Wideband Frequency Response with Acoustic shock protection, Mono (Monaural) and Stereo (Binaural) sound F.R : 100Hz ~ 7.5kHz
Mechanical	
Headset Weight	1.3 Ounces
Cord Length	2 meters
Connection	USB A-type
Environmental Characteristics	
Operating Temperature	0 °C ~ 40 °C
Storage temperature	-20 °C ~ +85 °C



S M5310-MOTH-PTT-NNC (NON-NOISE CANCELLING)

