



## Specifications For: Starkey SM 5400 Ultimate USB Headset with Push to Talk *Noise Cancelling Microphone*. S M5400-Both-PTT NC.

### Headset:

- **2 EAR** Durable Headband style.
- **This is a passive noise canceling mic**
- Acoustic shock protection receiver
- Microphone static shock protection
- Wideband frequency response, 20Hz to 7.5KHz
- Simple plug into USB port

### USB Adapter cord:

- USB 2.0 compliance
- Digital Signal Process(DSP)
- Wideband Frequency response 20Hz – 20KHz
- USB plug and play
- **In-line control board equipped PTT switch**

General Specifications	
Wearing Style	Over-the-Head
Cord Length	2 meters including the bottom cord.
Connector type	USB A-type connector
Quick Disconnect type	No QD (Direct Connection)
Weight	65g
Compatibility	Work with several Soft phones, MS Teams, MS Lync, Skype, all Window versions and all of voice-driven applications
Microphone	<b>Passive, Noise cancelling mic</b> with Static shock protection
Mic boom Arm type	Flexible PE bar
Earpiece	XL Oversized Leatherette cushions
Receiver	Wideband Frequency Response with Acoustic shock protection, Mono(Monaural) and Stereo(Binaural) sound
Color	Charcoal Grey
Packing Method	1) Bulk packing <ul style="list-style-type: none"> <li>- Individual PE Zipper bag</li> <li>- 100 bags in outer Carton box</li> </ul> 2) Individual Gift Box <ul style="list-style-type: none"> <li>- PE zipper bag in individual gift box</li> </ul>

	- 40 boxes in outer Carton box
Warranty	1 year
Compliance	RoHS
Approval	CE, FCC
Optional materials	Headset Hanger, Headset pouch, Leatherette or Foam cushion

## Microphone

Type	<b>Electret condenser Passive Mic</b>
Sensitivity	-44 +/- 3dB @ 1kHz, Vcc=2.0 VDC, RL=2.2K Ohms
Impedance	2.2K Ohms @ 1kHz
Frequency Response	100 ~ 10kHz
Max Input Sound Pressure Level	100dB SPL @1kHz
Harmonic Distortion	0.4% Max
Normal Current Consumption	400 $\mu$ A Max, Vcc=2.0 VDC
Operation Voltage	1.6 ~ 5.5 VDC

## Receiver

Size	36mm
Impedance	150 Ohms +/-15%
Frequency Response	Wideband Frequency Response with Acoustic shock protection, Mono(Monaural) and Stereo(Binaural) sound F.R : 100Hz ~ 7.5kHz

## Mechanical

Headset Weight	1.3 Ounces
Cord Length	2 meter
Connection	USB A-type

## Environmental Characteristics

Operating Temperature	0 °C ~ 40 °C
Storage temperature	-20 °C ~ +85 °C



**S M5400-Both-PTT-NC**

