



Specifications For: Starkey S M610 Elite BOTH (2EAR)- NNC MILITARY HEADSET. *Non-Noise Cancelling Microphone*. Push to Talk cord sold separately.

Headset:

- 2 EAR Durable Headband style.
- **This is a non-noise canceling mic**
- Acoustic shock protection receiver
- High-end receiver for “pure” hearing
- Microphone static shock protection
- Noise cancelling microphone for background noise reduction
- Soft headband T-bar for a comfortable wearing
- Wideband frequency response, 20Hz to 7.5KHz

General Specifications	
Wearing Style	Over-the-Head
Cord Length	3 meters including the bottom cord.
Connector type	Quick disconnect (QD)
Quick Disconnect type	Starkey QD
Weight	63g
Compatibility	Work with all kinds of single or multi-line and IP phones
Microphone	Dynamic (This is a non-noise canceling mic)
Mic boom Arm type	Flexible PE bar
Earpiece	Leatherette cushions
Receiver	Wideband Frequency Response with Acoustic shock protection, Monaural (SM600)
Color	Charcoal Grey
Packing Method	1) Bulk packing - Individual PE Zipper bag - 100 bags in outer Carton box
Warranty	1 years
Compliance	RoHS
Approval	CE, FCC, ACME
Optional materials	Headset Hanger, Headset pouch, Leatherette cushion

Microphone	
Type	Non-Noise Cancelling Mic , Electret condenser
Sensitivity	-44 +/- 3dB @ 1kHz, Vcc=2.0 VDC, RL=2.2K Ohms
Impedance	2.2K Ohms @ 1kHz
Frequency Response	100 ~ 10kHz
Max Input Sound Pressure Level	100dB SPL @1kHz
Harmonic Distortion	0.4% Max
Normal Current Consumption	400 μ A Max, Vcc=2.0 VDC
Operation Voltage	1.6 ~ 5.5 VDC
Receiver	
Size	36mm
Impedance	150 Ohms +/-15%
Frequency Response	Wideband Frequency Response with Acoustic shock protection, Mono(Monaural) and Stereo(Binaural) sound F.R : 100Hz ~ 7.5kHz
Mechanical	
Headset Weight	1.3 Ounces
Cord Length	2 meters
Connection	Quick Disconnect
Environmental Characteristics	
Operating Temperature	0 $^{\circ}$ C ~ 40 $^{\circ}$ C
Storage temperature	-20 $^{\circ}$ C ~ +85 $^{\circ}$ C

