

Excellent Work Partner for Phone and UC Communication

The Yealink WH62 is a new entry-level DECT wireless headset, with WH62 Dual and WH62 Mono two models. Work seamlessly with major UC platforms and integrate natively with Yealink IP phones. For crystal sound experience, Yealink Super Wideband Technology and Acoustic Shield Technology make you talk and hear clearly during phone calls and video conferencing. With easily on-ear control, interruption free, comfortable wearing, WH62 is a nice partner either for communicating or collaborating.



Acoustic Shield Technology



Optima Audio Experience



All Day Wearing Comfort



Built-in Ringer



Multiple Devices Connection



Customizable Busylight



Easy Management



Plug and Play



WH62 Mono Teams
WH62 Mono UC

Native Integration

No more EHS adapters needed, connect desk phone directly with one USB cable. And 2 Micro USB ports contained in the base, supporting connect to PC and IP phone simultaneously. Integrated deeply with Yealink IP Phones, you can just feel the crystal call experience at the moment of wearing WH62. Also work with popular UC platforms, achieving all-round collaboration.

Be Heard Crystal Clearly

With Yealink Acoustic Shield Technology, the two Microphones built in WH62 block the background noise automatically but ensure participant voice be heard clearly, greatly boost the communication efficiency.

Interruption Free

Busylight is enabled in WH62. With the light on the headset or BLT60 on the desk turning red, people around you would know that you are on the phone, instead of interrupting you unknowingly. Just stay focused on conversation, for higher efficiency, for better collaboration.

All-Day Comfort

Based on hundreds of headform evaluations and thousands of wearing comfort tests, WH62 well meets the ergonomic requirements. Besides, with premier soft leather cushions and lightweight design, you can wear it all day comfortably. For more workspace freedom, WH62 can also free you up to 160m away from the desk.



WH62 Dual Teams
WH62 Dual UC

- 2 Micro-USB connection
- Ringer on the base
- Supports busylight
- Yealink Acoustic Shield Technology
- Teams and Skype for Business compatible
- Talking Time up to 14h (Dual)/13h (Mono)
- Wireless range up to 160m

General

- 5 feature buttons
- 2 micro USB 2.0 port
- USB connectivity to PC and IP phone
- Integrated busylight LED indicator
- Boom arm adjustable: 320°
- Charging stand (for headset)

Battery

- Talk time: up to 13 hours (Mono), up to 14 hours (Dual)
- Standby time: 90 hours (Mono), 125 hours (Dual)
- Charging time: 2.5 hours (5V/1.2A)

DECT

- Wireless range: up to 160m/525 feet
- Secure DECT (level): Step C: authentication – DSAA2, encryption – DSC2 (128bit)
- Cordless Advanced Technology: CAT-iq 2.0

Audio (Headset)

- Microphone type: dual microphone
- Microphone sensitivity: -44.0+/-3 dBV

- Microphone frequency range: 100 Hz-10 kHz
- Speaker size: ϕ 28
- Speaker sensitivity: 92.5+/-3 dB, 0.179 V
- Speaker impedance: 32+/-4.8 Ω
- Speaker max output power: 10 mW
- Speaker frequency range: 20 Hz-20 kHz
- Speaker bandwidth - talk mode: wideband, 100Hz – 8kHz
- Speaker bandwidth - music mode: super wide-band, 20Hz-20kHz (Pending)
- Hearing Protection
 - Peak Block Protection (EN50332)
 - Australian G616 Protection (AU G616)
 - Daily Noise Exposure Protection

Audio (Base)

- Ringer size: ϕ 20
- Ringer sensitivity: 87+/-3 dB, 0.1 W, 0.1 M
- Ringer impedance: 8+/-1.2 Ω
- Ringer max output power: 1.5 W
- Ringer frequency range: 100 Hz-10 kHz

Easy Call Management

- Answer/End/Reject a call
- Volume up/down

- Microphone mute
- Move the microphone boom arm up to mute, or down to unmute

Package Features

- Package contents:
 - Base
 - Mono/dual headset
 - Power Adapter
 - 1.2m USB 2.0 Cable
 - 0.8m USB 2.0 Cable
 - Quick Start Guide
- Optional accessories:
 - Busylight BLT60
- WH62 Mono: Base: 208g, Headset: 80g
- WH62 Dual: Base: 208g, Headset: 127g
- Qty/CNT: 10 PCS
- N.W/CTN:
 - WH62 Mono: 6.60 kg; WH62 Dual: 7.10 kg
- Giftbox size: 260mm*203mm*112mm
- Carton Meas: 575mm*530mm*218mm

Compliance

CE  FC IC

Connection

